

ARMP6-72P-325

325 Watt



Guarantee positive power tolerance(0~+3%)



Module can bear snow loads up to 5400Pa and wind loads up to 2400Pa




High performance under low light conditions (Cloudy days, mornings and evenings)



Manufacturing facility certified by IOS 9001:2008 and IOS 14001:2004



Chubb products liability insurance, errors and omissions(E&O)insurance



Note: All products of ARMSolar have been certified by designated international organizations. For detailed information, please visit the company's official website

Certification



Electric Performance Typical Performance Characteristics

Short Circuit Current Temperature Coefficient	mA/°C	+5.2
Open Circuit Voltage Temperature Coefficient	V/°C	-0.1287
Maximum Power Temperature Coefficient	%/°C	-0.4514
Performance Warranty		
		90% output, 12 Years
		80% output, 25 Years

Industry-leading linear warranty

25 year product warranty




Typical Electronic Characteristics	325
Maximum power(pmax)	325
Power Tolerance	0÷+3%
Open Circuit Voltage(Voc)	46.3V
Short Circuit Current(Isc)	8.97A
Maximum Power Voltage(Vmp)	38.59V
Maximum Power Current(Imp)	8.44A
Module Efficiency	16.75%
Series Fuse Rating	15A
Terminal Box	IP65
Max.System Voltage	1000VDC
Cell Size and Series	Poly-Si crystalline 156x156mm(6inch) 72pcs (6x12)
NOTC-Nominal Operating Cell Temperature	-40÷+85°C
STC Condition	Irradiance level 1,000w/m ² , Spectrum AM 1.5, and Cell Temperature 25°C
Certifications	IEC61215, IEC61730, IEC62716, IEC61701-2012, IEC60364-4-41, IEC61724, IEC61853, IEC62446-2016 DIN EN 60068-2-68 ISO 9001:2015, ISO 14001:2004, ISO 17025:2005


Quality Assurance

1. Electrical insulation test.
7. Damp heat test.
2. Outdoor exposure test.
8. Robustness of terminations test.
3. Hot-spot endurance test.
9. Wet leakage current test.
4. UV-exposure.
10. Mechanical load test.
5. Thermal cycling test.
11. Hail impact test.
6. Humidity freeze test
12. Bypass diode thermal test.

Current-Voltage & Power-Voltage characteristics various irradiance levels



Physical Specifications



Dimension:
 Length: 1956 mm
 Width: 992 mm
 Depth: 40 mm
 Weight: 22.6 kg

Packing:
 27 pcs / carton

Loading Capacity:
 270 pcs / 20ft container
 594 pcs / 40ft container