

Module	FS-M60-285~270W			
Pmax	285W	280W	275W	270W
Size and number of cells	156.75*156.75mm, 60pcs/6*10			
Tolerance	0~+5%			
Vmp	31.80V	31.60V	31.40V	31.20V
Imp	8.96A	8.86A	8.76A	8.65A
Voc	38.90V	38.70V	38.50V	38.30V
Isc	9.54A	9.46A	9.38A	9.29A
Max.Syst.Oper.Voltage	1500V			
Glass	2.5mm high permeability, anti-reflective coating tempering glass			
Dimension	1658*992*6mm			
Weight	23kgs			
Operate Temp. Scope	-40/+85°C			
Warranty	10-year product warranty, 30-year linear power guarantee			
STC	Irradiance 1000 W/m ² , module temperature 25°C, AM=1.5			



Module	FS-M60-300~285W			
Pmax	300W	295W	290W	285W
Size and number of cells	156.75*156.75mm, 60pcs/6*10			
Tolerance	0~+5%			
Vmp	32.40V	32.20V	32.00V	31.80V
Imp	9.26A	9.16A	9.06A	8.96A
Voc	39.50V	39.30V	39.10V	38.90V
Isc	9.77A	9.69A	9.63A	9.54A
Max.Syst.Oper.Voltage	1500V			
Glass	2.5mm high permeability, anti-reflective coating tempering glass			
Dimension	1658*992*6mm			
Weight	23kgs			
Operate Temp. Scope	-40/+85°C			
Warranty	10-year product warranty, 30-year linear power guarantee			
STC	Irradiance 1000 W/m ² , module temperature 25°C, AM=1.5			

