

NM12-65L

12V 65Ah / 10hr rate**BATTERY**
Genergy

Introduction

Genergy NML (Long life) Series is designed for solar and renewable energy system. GEL electrolyte and AGM separator are applied in this series with feature of long service life. It is widely used in solar and wind power system, UPS and power utility.

Battery Features

- Increase durability and deep cycle ability for heavy demand applications
- Low self-discharge
- Fully tank formed plates
- Low impurity electrolyte
- Spill proof / leak proof
- Multi-position usage
- ABS case and cover VO upon request
- Very high purity lead

Electrical Specification

Design floating Life @ 20°C (68°F) 10 years

Nominal Capacity @ 25°C /77°F

20 hour rate 3.44A to 1.75Vpc 68.8 Ah

10 hour rate 6.55A to 1.75Vpc 65.5 Ah

Internal Resistance

(Fully charged battery @ 25°C /77°F) 8mΩ

Max. Discharge Current @ 25°C /77°F 600 A (5S)

Charge Methods: Constant voltage charge @ 25°C /77°F

Cycle Use 14.7 ~ 14.9V

Max. Current 17 A

Standby Use 13.6 - 13.8V

Operating Temperature Range -30 ~ 50°C

*Notes: battery voltage must be adjusted according to temperature.**Please refer to our recommendation.*




Self-Discharge

<3% of capacity declined per month @ 25°C (77°F).

Battery Picture & Terminal Layout



Terminal Type: T13



Dimension & Weight

Length	Dimension (± 2mm)			Weight (± 2%)
	Width	Height	Total Height	
327 mm	173 mm	167 mm	172 mm	20.4 kg
12.9 inch	6.8 inch	6.6 inch	6.8 inch	45.0 lbs

Typical Applications

○ Solar Energy System ○ Wind Energy System ○ Power Utility ○ UPS/EPS

Certificates



Constant Current Discharge (Amperes @ 25°C /77°F)

V/cell	10min	15min	20min	25min	30min	35min	40min	45min	50min	55min	1hr	2hr	3hr	4hr	5hr	10hr	20hr
1.60	156.8	119.7	103.4	87.1	74.7	66.3	61.9	57.4	53.4	49.6	46.4	25.25	18.56	15.36	12.76	6.71	3.52
1.65	148.9	113.7	98.7	83.8	72.7	64.6	60.3	56.1	52.3	48.8	45.8	24.87	18.21	15.04	12.47	6.68	3.51
1.70	142.7	109.0	94.8	80.7	70.4	62.4	58.4	54.3	50.7	47.3	44.5	24.12	17.79	14.68	12.18	6.61	3.47
1.75	136.2	103.9	90.6	77.2	67.8	60.1	56.3	52.5	49.1	46.0	43.5	23.55	17.40	14.36	11.92	6.55	3.44
1.80	129.1	98.6	86.1	73.7	65.2	57.7	54.1	50.5	47.4	44.5	42.2	22.79	16.98	14.01	11.63	6.38	3.35

Constant Power Discharge (Watts/cell @ 25°C /77°F)

V/cell	10min	15min	20min	25min	30min	35min	40min	45min	50min	55min	1hr	2hr	3hr	4hr	5hr	10hr	20hr
1.60	272.3	207.9	182.9	158.0	136.2	124.2	115.4	106.6	98.4	91.7	85.6	47.06	34.73	29.01	24.49	13.39	7.06
1.65	262.6	200.5	176.8	153.1	132.5	120.9	112.4	103.9	96.2	89.8	84.0	46.11	34.41	28.69	24.17	13.26	7.06
1.70	252.5	192.8	170.2	147.7	128.3	117.1	109.0	101.0	93.6	87.7	82.3	45.17	33.77	28.19	23.82	13.00	6.97
1.75	241.6	184.4	163.1	141.8	123.6	112.9	105.3	97.7	90.8	85.3	80.4	44.03	32.80	27.50	23.40	12.90	6.84
1.80	229.7	175.3	155.4	135.5	118.7	108.4	101.3	94.1	87.6	82.6	78.1	42.71	31.93	26.81	22.88	12.78	6.78

Subject to revision without notice. Please contact our sales representatives for latest version.

Web: www.genergybattery.com | Email: sales@genergybattery.com

Version NO.20181101

Page 1 of 2

NM12-65L

12V 65Ah / 10hr rate**BATTERY**
Genenergy

Graphs

