

NM12-90L

12V 90Ah / 10hr rate**BATTERY**
Genergy

Introduction

Genergy NML (Long life) Series is designed for solar and renewable energy system. GEL electrolyte and AGM separator are applied in this series with feature of long service life. It is widely used in solar and wind power system, UPS and power utility.

Battery Features

- Increase durability and deep cycle ability for heavy demand applications
- Low self-discharge
- Fully tank formed plates
- Low impurity electrolyte
- Spill proof / leak proof
- Multi-position usage
- ABS case and cover VO upon request
- Very high purity lead

Electrical Specification

Design floating Life @ 20°C (68°F) 10 years

Nominal Capacity @ 25°C /77°F

20 hour rate 4.89A to 1.75Vpc 97.8 Ah

10 hour rate 9.51A to 1.75Vpc 95.1 Ah

Internal Resistance

(Fully charged battery @ 25°C /77°F) 5mΩ

Max. Discharge Current @ 25°C /77°F 900 A (5S)

Charge Methods: Constant voltage charge @ 25°C /77°F

Cycle Use 14.7 ~ 14.9V

Max. Current 24 A

Standby Use 13.6 - 13.8V


Operating Temperature Range -30 ~ 50°C

*Notes: battery voltage must be adjusted according to temperature.**Please refer to our recommendation.*

Self-Discharge

<3% of capacity declined per month @ 25°C (77°F).

Battery Picture & Terminal Layout



Dimension & Weight

Length	Dimension (± 2mm)			Weight (± 2%)
	Width	Height	Total Height	
304 mm	175 mm	210 mm	215 mm	27.5 kg
12.0 inch	6.9 inch	8.3 inch	8.5 inch	60.6 lbs

Typical Applications

- Solar/Wind Energy System
- Power Utility
- UPS/EPS

Certificates



Constant Current Discharge (Amperes @ 25°C /77°F)

V/cell	10min	15min	20min	25min	30min	35min	40min	45min	50min	55min	1hr	2hr	3hr	4hr	5hr	10hr	20hr
1.60	217.4	166.0	143.4	120.8	102.2	96.8	90.3	84.3	78.8	71.5	69.1	37.45	26.64	22.13	18.28	9.74	4.93
1.65	206.5	157.6	136.9	116.2	99.5	94.3	88.0	82.4	77.2	70.3	68.1	36.72	26.13	21.66	17.86	9.69	4.93
1.70	197.9	151.1	131.5	111.9	96.3	91.1	85.2	79.7	74.8	68.2	66.3	35.48	25.53	21.15	17.44	9.60	4.93
1.75	188.8	144.1	125.6	107.1	92.6	87.7	82.1	77.1	72.6	66.4	64.8	34.50	24.97	20.69	17.06	9.51	4.89
1.80	179.1	136.7	119.4	102.2	89.0	84.2	78.9	74.2	70.0	64.3	63.0	33.26	24.37	20.18	16.64	9.26	4.84

Constant Power Discharge (Watts/cell @ 25°C /77°F)

V/cell	10min	15min	20min	25min	30min	35min	40min	45min	50min	55min	1hr	2hr	3hr	4hr	5hr	10hr	20hr
1.60	377.6	288.2	253.7	219.1	191.0	181.3	168.4	156.6	145.6	131.6	125.9	69.22	50.37	41.80	34.78	19.44	10.28
1.65	364.2	278.0	245.2	212.3	186.0	176.5	164.1	152.7	142.2	128.8	123.6	67.82	49.91	41.33	34.32	19.25	10.28
1.70	350.2	267.3	236.1	204.8	180.0	170.9	159.2	148.4	138.5	125.9	121.2	66.18	48.98	40.62	33.80	18.87	10.14
1.75	335.0	255.7	226.2	196.7	173.6	164.8	153.7	143.6	134.3	122.5	118.4	64.08	47.59	39.62	33.19	18.73	9.96
1.80	318.5	243.1	215.5	187.9	166.8	158.3	147.8	138.3	129.7	118.6	115.1	61.81	46.34	38.62	32.44	18.55	9.87

Subject to revision without notice. Please contact our sales representatives for latest version.

Web: www.genergybattery.com | Email: sales@genergybattery.com

Version NO.20180522

Page 1 of 2

NM12-90L

12V 90Ah / 10hr rate**BATTERY**
Genenergy

Graphs

