

NM12-120L

12V 120Ah / 10hr rate**BATTERY**
Genergy

Introduction

Genergy NML (Long life) Series is designed for solar and renewable energy system. GEL electrolyte and AGM separator are applied in this series with feature of long service life. It is widely used in solar and wind power system, UPS and power utility.


Battery Features

- Increase durability and deep cycle ability for heavy demand applications
- Low self-discharge
- Fully tank formed plates
- Low impurity electrolyte
- Spill proof / leak proof
- Multi-position usage
- ABS case and cover VO upon request
- Very high purity lead

Electrical Specification

Design floating Life @ 20°C (68°F)	10 years
Nominal Capacity @ 25°C / 77°F	
20 hour rate 6.18A to 1.75Vpc	123.6 Ah
10 hour rate 12.05A to 1.75Vpc	120.5 Ah
Internal Resistance	
(Fully charged battery @ 25°C / 77°F)	4.5mΩ
Max. Discharge Current @ 25°C / 77°F	1200 A (5S)
Charge Methods: Constant voltage charge @ 25°C / 77°F	
Cycle Use	14.7 ~ 14.9V
Max. Current	32 A
Standby Use	13.6 - 13.8V
Operating Temperature Range	-30 ~ 50°C
<i>Notes: battery voltage must be adjusted according to temperature. Please refer to our recommendation.</i>	
Self-Discharge	
<3% of capacity declined per month @ 25°C (77°F).	

Battery Picture & Terminal Layout



Dimension & Weight

Dimension (± 2mm)				Weight (± 2%)
Length	Width	Height	Total Height	
407 mm	173 mm	208 mm	237 mm	34.5 kg
16.0 inch	6.8 inch	8.2 inch	9.3 inch	76.1 lbs

Typical Applications

- Solar/Wind Energy System
- Power Utility
- UPS/EPS

Certificates



Constant Current Discharge (Amperes @ 25°C / 77°F)

V/cell	10min	15min	20min	25min	30min	35min	40min	45min	50min	55min	1hr	2hr	3hr	4hr	5hr	10hr	20hr
1.60	261.5	199.6	172.4	145.3	122.9	117.4	109.5	102.2	95.6	89.8	88.2	47.82	34.03	28.26	23.1	12.35	6.24
1.65	248.3	189.5	164.6	139.7	119.7	114.3	106.8	99.9	93.7	88.3	87.0	46.90	33.38	27.67	22.6	12.29	6.24
1.70	238.0	181.7	158.1	134.5	115.8	110.5	103.3	96.7	90.7	85.7	84.6	45.32	32.61	27.02	22.0	12.17	6.24
1.75	227.0	173.3	151.1	128.8	111.4	106.4	99.6	93.5	88.0	83.4	82.8	44.06	31.90	26.42	21.6	12.05	6.18
1.80	215.3	164.4	143.6	122.9	107.0	102.1	95.7	90.0	84.9	80.7	80.4	42.48	31.13	25.77	21.0	11.74	6.12

Constant Power Discharge (Watts/cell @ 25°C / 77°F)

V/cell	10min	15min	20min	25min	30min	35min	40min	45min	50min	55min	1hr	2hr	3hr	4hr	5hr	10hr	20hr
1.60	454.1	346.6	305.1	263.5	229.7	219.9	204.3	189.9	176.5	165.3	160.8	88.41	64.33	53.38	44.0	24.63	13.00
1.65	438.0	334.3	294.8	255.3	223.6	214.1	199.0	185.2	172.5	161.8	157.8	86.61	63.74	52.79	43.4	24.40	13.00
1.70	421.1	321.5	283.9	246.3	216.5	207.3	193.0	180.0	168.0	158.1	154.8	84.52	62.56	51.87	42.7	23.92	12.82
1.75	402.8	307.5	272.0	236.5	208.8	199.9	186.4	174.1	162.9	153.8	151.2	81.84	60.78	50.60	41.9	23.74	12.59
1.80	383.0	292.4	259.2	226.0	200.6	191.9	179.3	167.7	157.3	149.0	147.0	78.94	59.18	49.32	41.0	23.51	12.47

Subject to revision without notice. Please contact our sales representatives for latest version.

Web: www.genergybattery.com | Email: sales@genergybattery.com

Version NO.20181101

Page 1 of 2

NM12-120L

12V 120Ah / 10hr rate**BATTERY**
Genergy

Graphs

