


Sunny Inspire



Features

- Aesthetically using clear surface back-contact cells
- Cells with High conversion efficiency above 24%
- N-type solar cell has no LID naturally
- Lower hot spot temperature, higher safety
- Lower shadow-blocking loss
- Better weak illumination response

Electrical Specifications

Model Type	SI-B295
Peak Power (Pmax)	295W
Module Efficiency	22.42%
Maximum Power Voltage (Vmp)	22.8V
Maximum Power Current (Imp)	12.94A
Open Circuit Voltage (Voc)	26.1V
Short Circuit Current (Isc)	13.66A
Power Tolerance	-5% / + 10%
Maximum System Voltage	600V
Normal Operating Cell Temp.	46 °C (+/- 2)

Mechanical Specifications


Cell type	IBC
Number of cells	total 72 cells, 36 cells in series
Weight	14.9kg [32.85lbs]
Dimensions	1720 x 765 x 45mm [67.72 x 30.12 x 1.77in]
Frame	> 15 μ m clear anodized aluminum
Junction Box	IP 65 waterproof
Cables	4.00mm ² , 900mm
Connectors	MC4 compatible

Temperature Coefficients

Power	-0.290%/°C
Voltage	- 0.230%/°C
Current	+0.050%/°C

Warranties & Certifications

Warranties	5 years product warranty, 25 years limited power warranty of 80% of the minimum specified power rating
------------	--



Unit: mm [inch]

Note: All electrical parameters are rated at standard test conditions (irradiance of 1000W/m², AM 1.5G, cell temperature 77°F/25°C)

Caution: Read Safety and Installation Instruction before using this product.

2025 Sunny Inspire Limited. All right reserved. Specifications included in this datasheet are subject to change without notice.