


1500VDC光伏4.0面板式保险丝连接器 1500VDC PV 4.0 Panel Fuse Connector

产品规格: Product Specifications:


| | | | |
|--|----------------------------|--|--------------------------------|
| 绝缘材料 Insulation material | PPE/PA | 保险丝规格 Fuse Specification | 1A-50A |
| 额定电流 (不含保险丝) Rated current (Without fuse) | 50A | 安全等级 Safety degree | II |
| 额定电压 Rated voltage | 1500VDC | 阻燃等级 Flame class | UL94-V0 |
| 最大的测试电压(含保险丝) Maximum voltage (With fuse) | 1575V | 环境温度范围 Ambient temperature range | -40°C...+85°C (IEC) * |
| 连接器接触电阻 contact resistance | ≤ 0.25 mΩ | 温度上限 Upper limiting temperature | 110°C (IEC) |
| 金属导体材料 Contact material | 铜,镀锡 Copper, Tin plated | 适配电线规格 Suitable cable cross sections | 2.5~16mm ² /14~6AWG |
| 保护等级 Degree of protection | IP68(1m,1H) | 适配保险丝尺寸 (mm) Suitable for fuse size(mm) | 10*85 or 10/14*85 |
| Rated Impulse voltage 额定脉冲电压 | 16KV | 符合标准 Regulatory approval | TUV,CE |

图示: Drawing:


4PFC Panel fuse connector cable end





4PFF Panel fuse connector female end




4PFM Panel fuse connector male end



| 面板孔位尺寸 Panel Hole Size | 面板尺寸 Panel size | 解锁工具 Wrench tool |
|--|---|---|
|  |  |  |

安装参考尺寸(mm):
Installation reference size(mm):



保险丝额定电流:
Fuse Rated current:

| | | | | | | | | |
|------------|-----|-----|-----|------|-----|-----|-----|-----|
| 10*85mm | 1A | 2A | 3A | 3.5A | 4A | 10A | 15A | 20A |
| 10/14*85mm | 25A | 30A | 32A | 40A | 45A | 50A | | |

适配电线规格:
Suitable cable cross sections:

| B | 电线外径 (mm) Cable O.D. (mm) | 电线规格 (m ²) Cable Size (m ²) | 端子尺寸(mm ²) Terminal size(mm ²) | A(Ømm) | A'(Ømm) |
|-----|------------------------------|--|---|--------|---------|
| 6.6 | 4.5-5.4 | 2.5, 4.0, 6.0 | 2.5 | 4.2 | 4.2 |
| 7.2 | 5.2-6.8 | 6.0, 10.0 | 4 | 5.8 | 5.8 |
| 8.2 | 6.8-8.2 | 10 | 6 | | |
| 9.5 | 8.2-9.5 | 10.0 ~16.0 | 10-16 | 8 | 8 |

*建议最高使用环境温度为75摄氏度，且在75-85摄氏度下使用不能超过8小时。

*Recommended that the Max ambient temperature is 75°C, and not exceed 8 hours in 75-85°C.