



DC/AC PURE SINE WAVE INVERTER

CHNB-C2000-212 CHNB-C2000-224 CHNB-C2000-248

OUTPUT	RATED POWER	2000W		
	SURGE POWER	4000W		
	AC VOLTAGE AC	220V/230V ± 3%		
	WAVEFORM	PURE SINE WAVE		
	FREQUENCY	50 Hz		
	WAVE DISTORTION	3%		
INPUT	DC VOLTAGE DC	12v	24v	48v
	VOL.RANGE	10-15VDC	21-30VDC	42-60VDC
	UNLOAD CURRENT	< 0.7A		
	EFFICIENCY	85%	88%	90%
	DC CONNECTION	Cables with clips		
PROTECTION	LOW VOL.ALARM	10VDC ± 0.5V	20.5VDC ± 1V	44VDC ± 1V
	LOW VOL. SHUT DOWN	9.5VDC ± 0.5V	19.5VDC ± 0.5V	42VDC ± 1V
	OVERLOAD PROTECTION	shut off output		
	OVER VOL. SHUT DOWN	15.5V	30.5V	61.2V
	OVERHEAT PROTECTION	shut off output automatically		
PACKAGE	PRODUCT SIZE (MM)	458*166*90		
	PACKING SIZE(MM)	565*245*335		
	NET W. (kgs)	4.18kgs		
	GROSS W. (kgs)	4.68kgs		

