



# S Series (Plus) Single Phase Solar GTI

1.0KW/1.5KW/2.2KW/3.0KW  
3.6KW/4.4KW/5.0KW/6.0KW



Big LCD display



Power export limit



Compact and easy to install



Wifi/GPRS/Lan communication optional



### Simpler

Quick and easy single person installation  
Fault codes warning view on LCD display  
Built-in limiter optional



### Safer

comply with international quality standards  
tested by TÜV,BV,Dekra etc.



### Great reliability

IP65 ingress protection  
10+years R&D accumulation and support

ANYTIME, ANYWHERE

## REMOTE MONITORING PLATFORM

Monitor system performance in real-time via smartphone app or web portal using our advanced monitoring platform .

## S Series Single Phase



## Technology Data

Model No	S1000TL	S1500TL	S2200TL	S3000TL	S3600TL	S4400TL	S5000TL	S6000TL
<b>DC Side / Input Parameters</b>								
Max DC power (W)	1500W	2250W	3300W	4500W	5400W	6600W	7500W	7500W
Max DC voltage (Vdc)	550	550	550	550	550	550	550	550
Min System start/Shut down voltage (Vdc)	65/70	75/100	75/100	75/100	75/100	75/100	75/100	75/100
MPPT voltage range(Vdc)	70~500	100~500	100~500	100~500	100~500	100~500	100~500	100~500
Max. input current (A)	18A			22A			30A	
Max.input short circuit per MPPT	25A			30A			30A	
Number of MPP trackers				1				
Strings per MPP tracker				1				
<b>AC Side / Output Parameters</b>								
Nominal output power (W)	1000	1500	2200	3000	3600	4000	5000	6000
Maximum output power (W)	1100	1650	2420	3300	3960	4400	5500	6600
Nominal output voltage/range (V)	208,220,230,240/180~270							
AC grid frequency/range (Hz)	50Hz,60Hz(auto-selection) / 44Hz-55Hz; 54Hz-65Hz							
Maximum output current (A)	6	8	12	16	16	21	25	28
AC connection (with PE)	Single phase							
Current distortion(THDi)	<1.5%	<1.5%	<1.5%	<1.5%	<2.5%	<2.5%	<2.5%	<2.5%
Power factor	~1%(Adjustable from 0.8 leading to 0.8 lagging)							
<b>Efficiency</b>								
Maximum conversion efficiency	97.3%	97.3%	97.4%	97.5%	97.8%	97.8%	97.5%	97.6%
European efficiency	97.0%	97.0%	97.1%	97.2%	97.3%	97.3%	97.2%	97.3%
MPPT efficiency	99.9%	99.9%	99.9%	99.9%	99.9%	99.9%	99.9%	99.9%
<b>Safety and Protection</b>								
AFCI				yes				
DC reverse-polarity protection				yes				
Anti-islanding / Overvoltage protection				yes				
Short circuit protection				yes				
Leakage current protection				yes				
Grid monitoring / Ground fault monitoring				yes				
DC/AC side SPD(thermally protected)				yes				
<b>General Parameters</b>								
Dimension (L/W/H)(mm)	300/294/104				370/318.5/105.5			
Weight (kg)	5				7			
Embedded DC Switch					Optional			
Night power consumption (W)					< 0.2			
Isolation type					Transformerless			
Protection degree					IP65 according to IEC60529			
Operation temperature (°C)					-25 ~ +60			
Cooling concept					Smart Cooling			
Operating Altitude (m)					<2000m without power derating			
Acoustic noise level (dB)					< 25			
Display					Graphic LCD			
Communication Interface					Standard WIFI; RS485 (optional)			
Warranty					Standard 5 years; 7/10 years optional			
<b>Certificates and Approvals</b>								
CE-(EMC/LVD) : EN(IEC) 61000-1/-2/-3/; EN(IEC) 62109-1/-2								