

72 Half-cell Agrivoltaics HJT Module

325-335W

Through More Light IN, Gain More Greens.




HJT-0BB Technology

Shorter current transport path, better low-light performance, and higher power generation.



Dual Benefits

Perfectly matching the lighting requirements of crop cultivation, achieving dual benefits in electricity generation and cultivation.




For reference only



Complete System and Product Certifications:

- IEC61215, IEC61730
- ISO9001: 2015 Quality Management System
- ISO14001: 2015 Environment Management System
- ISO45001: 2018 Occupational Health and Safety
- IEC62941: 2019 Terrestrial Photovoltaic (PV) Modules-quality System for PV Module Manufacturing
- IEC/TS62994: 2019 Photovoltaic (PV) Modules Through the Life Cycle-environmental Health and Safety (EH&S) Risk Assessment-general Principles and Nomenclature



- * First year power degradation $\leq 1\%$
- * Annual power degradation (2-30 year) $\leq 0.3\%$
- * Power output until the 30th year $> 90.3\%$


HSN-210R-B72 325-335W

72-cell Bifacial HJT Solar Half Cell Module

- BloombergNEF Tier 1 PV module manufacturer
- Reinsurance underwritten by Ariel Re



Engineering Drawings

Unit: mm



I-V Curve

(HSN-210R-B72DSN335)



Temperature Characteristics

Temperature Coefficient of Pmax	-0.24%/°C
Temperature Coefficient of Voc	-0.22%/°C
Temperature Coefficient of Isc	+0.04%/°C

Operating Conditions

Nominal Operating Cell Temp.	44±2°C
Operating Temperature	-40~+85°C
Maximum System Voltage	DC1500V (IEC)
Maximum Series Fuse Rating	30A
Tolerance of Pmax	0~+3%
Power Selection	0~+5W
Bifaciality	90±5%
Safety Class	Class II

Mechanical Characteristics

Cell Type	HJT
No. of Cells	72(4x18)
Dimensions	1960x1134x30mm
Weight	26.9Kg
Junction Box	IP68
Cable	4mm²;+350/-450mm or customized; UV resistant
Connector	PV-H1 / MC4-Evo 2 / Others
Frame	Anodized aluminum alloy frame
Max Static Load (front side/rear side)	5400Pa / 2400Pa
Glass	Dual glass, 2.0mm

Electrical Characteristics

STC

HSN-210R-B72	DSN325	DSN330	DSN335
Maximum Power (Pmax/W)	325	330	335
Module Efficiency (%)	14.6	14.9	15.1
Voltage at Pmax (Vmp/V)	22.70	22.85	22.99
Current at Pmax (Imp/A)	14.32	14.45	14.58
Open Circuit Voltage (Voc/V)	27.07	27.23	27.39
Short Circuit Current (Isc/A)	15.02	15.15	15.28

STC: AM1.5, 1000W/m², 25°C.

BNPI

Maximum Power (Pmax/W)	364	370	375
Voltage at Pmax (Vmp/V)	22.78	22.93	23.07
Current at Pmax (Imp/A)	16.00	16.14	16.29
Open Circuit Voltage (Voc/V)	27.16	27.32	27.49
Short Circuit Current (Isc/A)	16.84	16.99	17.14

BNPI: AM1.5, 1000W/m², 135W/m², 25°C.

NOCT

Maximum Power (Pmax/W)	248	251	255
Voltage at Pmax (Vmp/V)	21.68	21.82	21.96
Current at Pmax (Imp/A)	11.45	11.55	11.65
Open Circuit Voltage (Voc/V)	25.84	25.99	26.14
Short Circuit Current (Isc/A)	12.00	12.11	12.21

NOCT: AM1.5, 800W/m², 20°C, 1m/s.

Packaging

	40'HQ
Modules Per Pallet	36
Pallets Per Container	24
Modules Per Container	864



ANHUI HUASUN ENERGY CO., LTD. All rights reserved © 2020-2025

NO.99 Qingliu Road, Economic and Technological Development Zone, Xuancheng, Anhui, China
 Tel: 0086-563-3318095 www.huasunsolar.com
 sales@huasunsolar.com customerservice@huasunsolar.com

With the development of technology and the iterative updating of products, the technical specification of products released by HUASUN in the future may differ from those listed in this datasheet. HUASUN reserves the right to change the technical specification of the products at any time without prior notice, and the technical specification of the products ordered by the customers are subject to the technical specification agreed upon in the legally binding contract signed by both parties. The final interpretation of the datasheet is reserved by HUASUN.

3.0_20250814