

NL Series Portable Solar Power System

Key Features:

- Portable and easy operation .
- DC output system with multiple interface can satisfy various demands.
- Charging and discharge independently.
- All controls adopt industrial chip and precision components, which can work normally in cold, high temperature, moisture condition.
- This system can be charged by AC adaptor also. User can use solar panel charge for battery and also user can choose the AC adaptor.

Model choose sheet

Model	NL5007	
Solar light kit	System voltage	12V
	Max.charge current	5A
	Double USB port	5V2.1A
	Solar&AC input	both
	DC 12V output port	2pcs or 3pcs or 4pcs
Solar panel	18V with 6m cable	max.50w(10w,15w,20w,30w optional)
Storage battery	12V lead acid battery	7Ah
AC charging adaptor	Input 100-240V,14.5V2A	optional
USB charger adaptor	10 different connectors	optional
Lighting source	LED bulbs 3W	2pcs or 3pcs or 4pcs
	Lighting cable with holder	2pcs or 3pcs or 4pcs
	Unit size	20*11*15cm

Model choose sheet

Model	NL5026	
Solar light kit	System voltage	12V
	Max.charge current	5A
	Double USB port	5V2.1A
	Solar&AC input	both
	DC 12V output port	4pcs or 6pcs
Solar panel	18V with 6m cable	max.50w(10w,15w,20w,30w optional)
Storage battery	12V lead acid battery	26Ah
AC charging adaptor	Input 100-240V,14.5V2A	optional
USB charger adaptor	10 different connectors	optional
Lighting source	LED bulbs 3W	4pcs or 6pcs
	Lighting cable with holder	4pcs or 6pcs
	Unit size	23*13.5*22cm

Micro Inverter

SVT Series 250W-500W



Technical Data

Model	SVT248
Input Data (DC)	
Recommended maximum input power (STC)	250W
Maximum input DC voltage	54V
Start voltage	24V
Peak power tracking range	28V~42V
Operating range	18V~54V
Maximum DC short circuit current	15A
Maximum input current	9.5A
Output Data (AC)	
Rated output power	248W
Maximum output current	1.07A
Nominal voltage	220V/230V/240V
Nominal frequency	50Hz/60Hz
Power factor	>0.99
Total Harmonic Distortion	<3%
Maximum units per branch	20
Efficiency	
Peak inverter efficiency	95.60%
EURO weighted efficiency	95%(according to the EN50530)
Nighttime power consumption	100mW
Mechanical Data	
Enclosure environmental rating	IP65
Operating temperature range	-40°C ~ +65°C

The SVT248 Microinverter as a cutting-edge spokesman for the microinverters in the new era, has full sincerity and devotion to stability, details and more advanced tech. SVT248 seeks to enable best improved solar energy harvest, highest possible reliability, much simplified installation and most efficient management of solar power systems.

Each SVT248 is individually connected to one solar panel with every MPPT(Maximum Power Point Tracking) respectively for every panel. This unique configuration minimizes the negative impact from environment such as shading, dust, orientation or panel aging and eliminates the possibility of single-point failure, thus improving the system's harvest to the largest extent.

Key Features:

- High-quality energy harvest with high MPPT accuracy.
- Concentrated reliability and stability.
- No single-point failure.
- Improved safety with integrated complete set of protection functions.
- Lifetime free remote monitoring at solar panel's level.
- Flexibly adapted to almost all 60-cell or 72-cell panels.
- Easy installation.
- Long life time.

