

# Technical Data

Product: Mono-crystalline silicon solar PV module

Rated Power: **30Wp**

## 1 Electrical Characteristics:

At STC: 1000W/m<sup>2</sup>, Cell temperature 25°C, AM1.5

Module type	RT30WM
Rated Power	30Wp
Tolerance	0~+3%
Open Circuit Voltage (V <sub>oc</sub> )	22.6V
Short Circuit Current (I <sub>sc</sub> )	1.76A
Max. Power Voltage (V <sub>m</sub> )	18.4V
Max. Power Current (I <sub>m</sub> )	1.63A
Temperature coefficients of I <sub>sc</sub> (%)	0.10/°C
Temperature coefficients of V <sub>oc</sub> (%)	-0.33/°C
Temperature coefficients of P <sub>m</sub> (%)	-0.23/°C
Module Efficiency (%)	≥13.07%
package	400pcs/pallet

## 2 Overall Characteristics:

- 36 Monocrystalline photovoltaic Cells per Module
- Size:656\*350\*25mm
- Weight: 2.5kg
- Glass 3.2mm tempered
- EVA encapsulated
- Glass Foil Sandwich Laminated
- Sandblasting anodizing Aluminum frame
- IEC 5400Pa tested
- Hail up to 25mm diameter,80 Km/h tested
- Temperature Range: -40 to +85°C
- Nominal operating cell temperature (NOCT): 47°C

## 3 Electrical connection:

- Junction Box IP67
- 2 Bypass Diodes, nominal current 20A
- Solar Cable 4mm<sup>2</sup> 900mm with MC4 connectors
- Module connection max 715 DC in series
- Limiting reverse current I<sub>r</sub>=0.2A

## 4 Certificates

- TUV IEC 61215
- TUV IEC 61730-01/02
- CE
- ISO 9001:2015
- ISO 14001:2015

