

NSFG150S08 48V150Ah

LiFePO₄ Lithium Battery

Longer Cycle Life: Offers up to 15 times longer cycle life and 5 times longer float/calendar life than lead acid battery.

Lighter Weight: About 40% weight of a comparable lead acid battery, save up to 60% in weight.

Quick Charge: Short charge time compared with lead acid battery.

Low Self-Discharge: Lower self-discharge compared with lead acid battery, longer storage time without recharging.

Superior Safety: Multi-protection methods built inside to protect the battery from overcharge, over discharge and short circuit situation.


High Efficient: Higher round-trip energy efficiency of the average (92%) than lead acid battery 80% (discharge from 100% to 0% and back to 100% charged).



Specifications

Nominal voltage		48V
Nominal capacity		150Ah
Dimensions	Length	442±2mm (17.40inch)
	Width	480±2mm (18.89inch)
	Height	311±2mm (12.24inch)
	Total height	311±2mm (12.24inch)
Approx. weight		70.5kg (155.42lbs)±2.5kg


Outer dimensions (mm)




Characteristics

Electrical Parameters (25°C)	Rated Voltage	48V
	Rated Capacity (C ₅)	150Ah@25°C
	Energy	7200Wh
	Months Self Discharge	<3%
	Charge Efficiency	99.5%@ 0.2C
	Discharge Efficiency	97%@ 1C
Terminal Diameter		M8
Internal resistance (Fully charged, 25°C)		≤80mΩ
Cycle life		>3000 cycles @ 0.2C 100%D.O.D
Capacity affected by temperature	40°C	101%
	25°C	100%
	0°C	90%
	-10°C	75%
Self heat function		Option available
Nominal operating temperature		25°C±3°C (77°F± 5°F)
Operating temperature range	Discharge	- 20°C~ 60°C (-4°F ~ 140°F)
	Charge	0°C~ 45°C (32°F ~ 113°F)
	Storage	0°C~ 40°C (32°F ~ 104°F)
Water Dust Resistance		IP50
Charge Voltage		54.7V
Standard Charge Mode (25°C±2°C, <75%RH)		0.2CA Constant Current to 54.7V, then Constant Voltage 54.7V until the current drops to 0.02CA, before use, rest 30 minutes
Charge Current		30A
Maximum Charge Current		75A
Charge Cut off Voltage		54.7V
Continuous Discharge Current		100A
Maximum Pulse Current		200A (<500us)
Discharge Cut Off Voltage		42V
Communicate Protocol (optional)		RS485/RS232/CAN
SOC (optional)		LED/PC Software
Application connection		1 string 1 parallel
Mechanical	Cells	15 Strings
	Container	Metal


● Discharge characteristics (25°C)




● Temperature affect on discharge characteristics (0.5C)




● State of Charge Curve (25°C)




● Charge characteristics (25°C)



● Cycle life on D.O.D (25°C)



● Self Discharge Characteristics Curve



Note 2: The above curves are based on laboratory testing data @ 25°C 40%RH.