

NEW

30-35K

SOLARATOR SERIES

Operates Seamlessly with Generator: Experience Uninterrupted Power, Even in Areas with Grid Instability

S6-EH3P(30-35)K-H-LV(21A)

Three Phase | High Voltage



10 Unique Advantages

- ★ Supports up to 2x rated PV input, maximizing solar energy utilization
- ★ Supports a maximum string input current of 21A, ensuring compatibility with high-power PV modules
- ★ Compatible with 100-314Ah battery modules, reducing overall system costs
- ★ Supports fast battery charging with a maximum charging current of 160A
- ★ Two independent battery ports for flexible configurations and easy capacity expansion
- ★ Delivers 160% overload for 2s in off-grid mode, ensuring stable startup of heavy loads
- ★ Offers flexible control for weak grid and genset-hybrid scenarios, reducing investment costs
- ★ SolisCloud: Smart remote control, AI optimisation, and instant troubleshooting - all in one platform
- ★ Integrates PV and storage for demand management and anti-reverse flow functions
- ★ Provides dynamic reactive power compensation to improve grid power factor and reduce reactive power charges

6 Leading Advantages

- Supports both DC and AC coupling, for flexible retrofits and system expansions
- Ensures reliable backup power across diverse scenarios through battery reserve management
- Extends supply time for critical loads with intelligent load prioritization
- Offers a versatile three-in-one interface for seamless integration of on-grid PV, wind power, and diesel generators
- Achieves on- and off-grid transitions in less than 10ms, ensuring an uninterrupted power supply
- Supports multi-unit parallel operation up to 350kW (Solis STS cabinet recommended for systems over 6 units)

PHILIPPINES

t: +86 574 6580 2188 (sales) +63 2 8372 7945 (service)

e: sales@ginlong.com phservice@solisinverters.com

w: solisinverters.com



DATASHEET

Models	30K	35K
Input DC (PV side)		
Recommended max. PV array size	60 kW	70 kW
Max. usable PV input power	60 kW	70 kW
Max. input voltage	1000 V	
Rated voltage	600 V	
Start-up voltage	180 V	
MPPT voltage range	150 - 850 V	
Max. input current	3 × 42 A	
Max. current per DC input	42 A	
Max. short circuit current	3 × 60 A	
MPPT number / Max. input strings number	3 / 6	
Battery		
Battery type	Li-ion	
Battery voltage range	150 - 800 V	
Max. charge / discharge current	80 A × 2	
Number of battery ports	2	
Max. charge / discharge power of each input	33 kW	35 kW
Communication	CAN / RS485	
Output AC (Back-up)		
Rated output power	30 kW	35 kW
Max. apparent output power	1.6 times of rated power, 2 s; 1.5 times of rated power, 10 s	
Back-up switch time	< 10 ms	
Rated output voltage	3/(N)/PE, 127 V / 220 V; 3/(N)/PE, 133 V / 230 V	
Rated frequency	50 Hz / 60 Hz	
THDv (@linear load)	< 2%	
Input AC (Grid side)		
Max. input current	152 A / 152 A	
Input AC (Generator)		
Max. input power	30 kW	35 kW
Rated input current	78.7 A / 75.3 A	91.8 A / 87.8 A
Rated input voltage	3/(N)/PE, 127 V / 220 V; 3/(N)/PE, 133 V / 230 V	
Rated input frequency	50 Hz / 60 Hz	
Output AC (Grid side)		
Rated output power	30 kW	35 kW
Max. apparent output power	30 kVA	35 kVA
Rated grid voltage	3/(N)/PE, 127 V / 220 V; 3/(N)/PE, 133 V / 230 V	
Rated grid frequency	50 Hz / 60 Hz	
Rated grid output current	78.7 A / 75.3 A	91.8 A / 87.8 A
Power factor	> 0.99 (0.8 leading - 0.8 lagging)	
THDi	< 3%	
Efficiency		
Max. efficiency	96.3%	
EU efficiency	95.5%	
Battery charged efficiency	97.4%	
Battery discharged efficiency	95.8%	
Protection		
Surge protection	DC Type II / AC Type II	
Output over current protection	Yes	
Integrated DC switch	Yes	
DC reverse-polarity protection	Yes	
Protection class / Over voltage category	I / PV II, battery II, AC III	
Integrated AFCI 2.0	Optional	
General Data		
Max. allowable phase imbalance (grid & back-up)	100%	
Max. power per phase (grid & back-up)	33%	
Dimensions (W × H × D)	530 × 880 × 290 mm	
Weight	76 kg	
Topology	Transformerless	
Operating ambient temperature range	-25 ~ +60°C	
Relative humidity	0 - 100%	
Ingress protection	IP66	
Cooling concept	Intelligent fan-cooling	
Max. operation altitude	4000 m	
Grid connection standard	G99, VDE-AR-N 4105/VDE V 0124, EN 50549-1/EN 50549-10, PTPIREE, VDE 0126/XP C15/VFR:2019, NTS 631/RD 1699/RD 244/UNE 217002, CEI 0-21, C10/11, NRS 097-2-1, TOR, EIFS 2018.2, IEC 62116, IEC 61727, DEWA, MEA, PEA, PORTARIA N° 140/PORTARIA N° 515	
Safety / EMC standard	IEC/EN 62109-1/-2, IEC/EN 61000-6-2/-4, EN 55011	
Features		
PV connection	MC4 connector	
Battery connection	Terminal connector	
AC connection	OT terminal	
Display	7.0" LCD display & Bluetooth + APP	
Communication	CAN, RS485-115200, Optional: Wi-Fi, Cellular, LAN	