

HYBRID SOLAR INVERTER/SINGLE PHASE

AN-HYI-E 3KW/6KW



MODEL	AN-HYI-E3000W	AN-HYI-E6000W
Phase	1-phase in /1-phase out	
Maximum PV Input Power	4500W	9000W
Rated Output Power	3000W	6000W
Maximum Charging Power	3000W	6000W

GRID-TIED OPERATION

PV INPUT(DC)		
Maximum DC Voltage	/	500Vdc
Start-up Voltage/Initial Feeding Voltage	/	90Vdc/120Vdc
MPPT Voltage Range	/	60-450Vdc
Number of MPP Trackers/Maximum Input Current	/	2/18A
GRID OUTPUT(AC)		
Nominal Output Voltage	/	220/230/240VAC
Output Voltage Range	/	184-264.5VAC or 195.5-253VAC or 184-264.4VAC(Selectable)

Nominal Output Current	/	26.1A
Power Factor	/	>0.99
Maximum Conversion Efficiency(DC/AC)	/	97%

OFF-GRID OPERATION

AC INPUT		
AC Start-up Voltage/Auto Restart Voltage	120-140VAC/180VAC	
Acceptable Input Voltage Range	90-280VAC	
Frequency Range	50Hz/60Hz(Auto sensing)	
Maximum AC Input Current	18A	40A
PV INPUT(DC)		
Maximum DC Voltage	500Vdc	520Vdc
MPPT Voltage Range	50Vdc-450Vdc	
Number of MPPT Tracks/Maximum Input Current	1/18A	2/18A
BATTERY MODE OUTPUT(AC)		
Nominal Output Voltage	220/230/240VAC	
Output Waveform	Pure Sine Wave	
Efficiency(DC to AC)	93%	

HYBRID OPERATION

PV INPUT(DC)		
Maximum DC Voltage	500Vdc	
Start-up Voltage/Initial Feeding Voltage	90Vd/120Vdc	
MPPT Voltage Range	50Vdc-450Vdc	
Number of MPPT Trackers/Maximum Input Current	1/18A	2/18A
GRID OUTPUT(AC)		
Nominal Output Voltage	220/230/240VAC	
Output Voltage Range	184-264.5VAC or 195.5-253VAC or 184-264.4VAC(Selectable)	
Nominal Output Current	13A	26.1A
AC INPUT		
AC Start-up Voltage/Auto Restart Voltage	120-140VAC/180VAC	
Acceptable Input Voltage Range	90-280VAC or 170-280VAC	
Maximum AC Input Current	16A	40A
BATTERY MODE OUTPUT(AC)		
Nominal Output Voltage	220/230/240VAC	
Efficiency(DC to AC)	93%	
BATTERY& CHARGER		
Nominal DC Voltage	24Vdc	48Vdc
Maximum Solar Charging Current	100A	135A
Maximum AC Charging Current	100A	135A
Maximum Charging Current	100A	135A

PHYSICAL

Dimension, D xWx H(mm)	451x353x160	471x444x200
Net Weight (kg)	12.3	18.2

GENERAL

Parallel Function	/	Yes, 6 units
Communication Port	RS232/RS485/Wi-Fi	RS232/RS485/CAN/Wi-Fi/Dry Contact
Humidity	5% to 95% Relative Humidity(Non-condensing)	
IP Degree	IP65	
Operating Temperature	-10°C~50°C	
Storage Temperature	-15°C~60°C	