

# **+ Ultra** *new range*

➔ Photovoltaic module  
**A-255P / A-260P / A-265P (TYCO 3.2)**



**+ UltraPositive tolerance**  
Positive 0 / +5 Wp

**+ UltraQuality Criteria**  
Anti Hot-Spot

**+ UltraWarranty**  
10-year product warranty

**+ UltraReliability**  
In the market since 1979

**+ UltraResistance**  
3.2 mm tempered glass

**+ UltraTES**  
Cell-to-cell electrical verification



A unique system  
in the market,  
patented by  
Atersa.





Electrical characteristics (STC: 1kW/m<sup>2</sup>, 25°C±2°C and AM 1,5)\*

	A-255P	A-260P	A-265P
Rated Power (0/+5 W)	255 W	260 W	265 W
Module efficiency	15,66%	15,97%	16,27%
Peak-Point Current of Maximum Power (Imp)	8,29 A	8,35 A	8,40 A
Peak-Point Voltage of Maximum Power (Vmp)	30,76 V	31,20 V	31,55 V
Short-circuit Current (Isc)	8,88 A	8,95 A	9,01 A
Open Current Voltage (Voc)	37,80 V	37,98 V	38,14 V

Thermal parameters

Isc (α) Temperature Coefficient	0,04% /°C
Voc (β) Temperature Coefficient	-0,32% /°C
P (γ) Temperature Coefficient	-0,43% /°C

Physical characteristics






Dimensions (mm ± 2 mm)	1645x990x40
Weight (0,5 kg)	19,2
Surface area (m <sup>2</sup> )	1,63
Cell type (± 1 mm)	Polycrystalline 156x156 mm (6 inches)
Cells in series	60 (6x10)
Front glass	Ultra-clear 3.2 mm tempered glass
Frame	anodized aluminium alloy or Polyester-coated
Connection box	TYCO IP67
Cables	Solar Cable 4 mm <sup>2</sup> 1.200 mm
Connectors	TYCO PV4

Operating range


Temperature	-40°C to +85°C
Maximum System Voltage / Protection	1000 V / CLASS II
Maximum Wind Load / Snow Load	2400 Pa (130 km/h) / 5400 Pa (551 kg/m <sup>2</sup> )
Max. Reverse Current (IR)	15,1 A

\*Electrical specifications measured in STC. NOCT: 47±2°C.  
Tolerance measures STC: ±3% (Pmp); ±10% (Isc, Voc, Imp, Vmp).

A-260P curves model



- Modules per box: **25 units**
- Weight per pallet: **495 kg**
- A 40-foot container can hold 25 boxes: **625 panels**
- A 40-foot HC container can hold 26 boxes: **650 panels**
- A 20-foot container can hold 10 boxes: **250 panels**
- A TAUTLINER truck can hold 30 boxes: **750 panels**



NB: The data contained in this documentation are subject to modification without prior notification.

➔ [www.atersa.com](http://www.atersa.com) • [atersa@elecnor.com](mailto:atersa@elecnor.com)  
Madrid +34 915 178 452 • Valencia +34 961 038 430

Latest revision: **28/04/17**  
Ref.: **E-MU-6P (3) 6x10-B (TY 3.2)**  
© **Atersa SL, 2016**

