

AU-60M


POWER RANGE
320W~330W

CELL SIZE
158.75*158.75mm




JUNCTION BOX

Waterproof protection grade:IP67/IP68
Safety Level: Class II
Maximum System Voltage: 1500V/1000V
outstanding waterproof level ·
Effectively resist harsh environments




Frame

Strong machinical load
resistance up to 5400Pa
Anodic oxidation layer resistant to
chemical corrosion available
in silver and black



5BB



9BB



MBB Cells

Absorbing current and reducing mismatched loss.



Outstanding low light performance

Available for outputting more power under low light conditions such as haze,cloudy or rainy days.



Anti-reflective glass

Increasing light absorption and reducing the loss of power.



Excellent performance of PID resistance


The performance of PID resistance(Potential Induced Degradation) passed the standard of TUV Nord.

QUALIFICATIONS AND CERTIFICATES



· IEC61215 / · IEC61730

WARRANTY



12 YEARS

Guarantee on product material and workmanship

30 YEARS

Linear Power output warranty


AUSTA ENERGY
www.austagroup.com

AUSTA ENERGY established in 2008, is a high-tech enterprise integrating R&D, production and sales of solar energy products. It is committed to the overall solution of distributed photovoltaic system and provides services from consulting, design, construction, financing to intelligent operation and maintenance.

AUSTA has 3 production sites in China and branches and representative offices in more than 10 countries overseas. Products include solar cells, modules, On/Off grid solar system, solar pump and other solar related applications. Our products have passed many international certifications such as TUV, MCS, CEC, IEC, ISO, CE, CQC and so on. With excellent quality, our products are exported to more than 100 countries of the world.

Since its establishment, AUSTA has always followed the idea of "Smart energy, Lightning future". It has followed the steps of "the Belt and Road Initiative", we bring bright light to the countries and people who are short of electricity. Sharing the concept of modern civilization, and building a green home together.

PV DRAWINGS



ELECTRICAL DATA (STC)

Model Type	AU-320W30M	AU-325W30M	AU-330W30M
Peak Power(Pmax)	320.00	325.00	330.00
Maximum Power Voltage(Vmp)	32.84	32.94	33.04
Maximum Power Current(Imp)	9.75	9.87	9.99
Open Circuit Voltage(Voc)	40.23±3%	40.35±3%	40.47±3%
Short Circuit Current(Isc)	10.27±3%	10.39±3%	10.52±3%
Module Efficiency(%)	19.26	19.56	19.86

* STC: irradiance 1000 W/m², AM 1.5, and cell temperature of 25°C

ELECTRICAL DATA (NOCT)



Model Type	AU-320W30M	AU-325W30M	AU-330W30M
Peak Power(Pmax)	238.00	241.00	245.00
Maximum Power Voltage(Vmp)	30.71	30.80	30.90
Maximum Power Current(Imp)	7.75	7.83	7.93
Open Circuit Voltage(Voc)	37.83±3%	37.95±3%	38.07±3%
Short Circuit Current(Isc)	8.22±3%	8.30±3%	8.41±3%

* NOCT: irradiance 800 W/m², AM 1.5, ambient temperature 20°C, wind speed 1 m/s

TEMPERATURE & MAXIMUM RATING

Maximum System Voltage (V)	1500/1000 V
Maximum Series Fuse Rating (A)	20 A
Power Tolerance	0~+3 W
Pmax Temperature Coefficients (W/°C)	-0.400 %/°C
Voc Temperature Coefficients (V/°C)	-0.290 %/°C
Isc Temperature Coefficients (A/°C)	+0.048 %/°C
NOCT Nominal Operating Cell Temperature (°C)	45±2 °C
Operating and Storage Temperature (°C)	-40~+85 °C

IV CURVE (330W)



MECHANICAL CHARACTERISTICS

Cell Type	158.75*158.75 Mono
No. of Cells	60 (6*10)
Dimensions	1658*1002*35mm
Weight	18.60kg
Front Glass	3.2mm high transmission, low iron, tempered glass
Frame	Anodized Aluminium Alloy
Junction box	IP67/IP68 3diodes
Output cables	4mm ² cable 35cm (Including MC4 connector)
MaxWind Load/Snow Load	2400Pa/5400Pa

PACKING WAY

20FT container	12 Packages/372pcs
40HQ container	28 Packages/952pcs

Austa



ZHEJIANG AUSTA GREEN ENERGY TECHNOLOGY CO., LTD

ADD: NO.128 Haichuan Rd, Jiangbei Dist., Ningbo, China

Tel : 86-574-87915068

Cell: 86-13566302808

E-mail : sales@austagroup.com

The company reserves the right of final interpretation, November 2020 edition