

# HiHero

**HIGH EFFICIENCY HETEROJUNCTION CELL TECHNOLOGY**

**405 W ~ 430 W**

**CS6R-405 | 410 | 415 | 420 | 425 | 430H-AG**

## MORE POWER



Module efficiency up to 22.0%, maximize the use of rooftop space



No B-O LID, excellent anti-LeTID & anti-PID performance. Low power degradation, high energy yield



Leading temperature coefficient (Pmax): -0.26%/°C, increases energy yield in hot climate



Better shading tolerance

## MORE RELIABLE



Minimizes micro-crack impacts



Heavy snow load up to 5400 Pa, enhanced wind load up to 2400 Pa\*



**Industry Leading Product Warranty on Materials and Workmanship\***



**Linear Power Performance Warranty\***

**1<sup>st</sup> year power degradation no more than 2%  
Subsequent annual power degradation no more than 0.45%**

\*According to the applicable Canadian Solar Limited Warranty Statement.

## MANAGEMENT SYSTEM CERTIFICATES\*

ISO 9001:2015 / Quality management system  
ISO 14001:2015 / Standards for environmental management system  
ISO 45001: 2018 / International standards for occupational health & safety

## PRODUCT CERTIFICATES\*

IEC 61215 / IEC 61730 / MCS  
IEC 61701 / IEC 62716  
Take-e-way




\* The specific certificates applicable to different module types and markets will vary, and therefore not all of the certifications listed herein will simultaneously apply to the products you order or use. Please contact your local Canadian Solar sales representative to confirm the specific certificates available for your Product and applicable in the regions in which the products will be used.

**CSI Solar Co., Ltd.** is committed to providing high quality solar products, solar system solutions and services to customers around the world. Canadian Solar was recognized as the No. 1 module supplier for quality and performance/price ratio in the IHS Module Customer Insight Survey, and is a leading PV project developer and manufacturer of solar modules, with over 59 GW deployed around the world since 2001.


\* For detailed information, please refer to the Installation Manual.

## ENGINEERING DRAWING (mm)


### Rear View



### Frame Cross Section A-A



## CS6R-415H-AG / I-V CURVES



## ELECTRICAL DATA | STC\*

CS6R	405H-AG	410H-AG	415H-AG	420H-AG	425H-AG	430H-AG
Nominal Max. Power (Pmax)	405 W	410 W	415 W	420 W	425 W	430 W
Opt. Operating Voltage (Vmp)	33.5 V	33.8 V	34.0 V	34.3 V	34.5 V	34.7 V
Opt. Operating Current (Imp)	12.08 A	12.14 A	12.20 A	12.26 A	12.32 A	12.38 A
Open Circuit Voltage (Voc)	39.7 V	40.0 V	40.2 V	40.4 V	40.7 V	40.9 V
Short Circuit Current (Isc)	12.88 A	12.94 A	13.00 A	13.09 A	13.15 A	13.21 A
Module Efficiency	20.7%	20.9%	21.2%	21.4%	21.7%	22.0%
Operating Temperature	-40°C ~ +85°C					
Max. System Voltage	1500V (IEC) or 1000V (IEC)					
Module Fire Performance	CLASS C (IEC61730)					
Max. Series Fuse Rating	25 A					
Application Classification	Class A					
Power Tolerance	0 ~ + 10 W					

\* Under Standard Test Conditions (STC) of irradiance of 1000 W/m<sup>2</sup>, spectrum AM 1.5 and cell temperature of 25°C.

## MECHANICAL DATA

Specification	Data
Cell Type	HJT cells
Cell Arrangement	108 [2 X (9 X 6)]
Dimensions	1727 X 1134 X 35 mm (68.0 X 44.6 X 1.38 in)
Weight	23.0 kg (50.7 lbs)
Front Glass	2.0 mm heat strengthened glass
Back Glass	1.6 mm heat strengthened glass
Frame	Anodized aluminium alloy
J-Box	IP68, 3 bypass diodes
Cable	4 mm <sup>2</sup> (IEC)
Cable Length (Including Connector)	Portrait: 410 mm (16.1 in) (+) / 290 mm (11.4 in) (-) (supply additional jumper cable: 2 lines / Pallet) ; landscape: 1100 mm (43.3 in)*
Connector	T4 series or MC4-EVO2
Per Pallet	30 pieces
Per Container (40' HQ)	780 pieces

\* For detailed information, please contact your local Canadian Solar sales and technical representatives.

## ELECTRICAL DATA | NMOT\*

CS6R	405H-AG	410H-AG	415H-AG	420H-AG	425H-AG	430H-AG
Nominal Max. Power (Pmax)	310 W	314 W	318 W	322 W	326 W	330 W
Opt. Operating Voltage (Vmp)	32.2 V	32.4 V	32.7 V	32.9 V	33.1 V	33.3 V
Opt. Operating Current (Imp)	9.64 A	9.69 A	9.74 A	9.79 A	9.83 A	9.88 A
Open Circuit Voltage (Voc)	37.9 V	38.1 V	38.3 V	38.6 V	38.8 V	39.0 V
Short Circuit Current (Isc)	10.37 A	10.42 A	10.47 A	10.54 A	10.59 A	10.64 A

\* Under Nominal Module Operating Temperature (NMOT), irradiance of 800 W/m<sup>2</sup> spectrum AM 1.5, ambient temperature 20°C, wind speed 1 m/s.

## TEMPERATURE CHARACTERISTICS

Specification	Data
Temperature Coefficient (Pmax)	-0.26 % / °C
Temperature Coefficient (Voc)	-0.24 % / °C
Temperature Coefficient (Isc)	0.04 % / °C
Nominal Module Operating Temperature	41 ± 3°C

## PARTNER SECTION



\* The specifications and key features contained in this datasheet may deviate slightly from our actual products due to the on-going innovation and product enhancement. CSI Solar Co., Ltd. reserves the right to make necessary adjustment to the information described herein at any time without further notice. Please be kindly advised that PV modules should be handled and installed by qualified people who have professional skills and please carefully read the safety and installation instructions before using our PV modules.

CSI Solar Co., Ltd.

199 Lushan Road, SND, Suzhou, Jiangsu, China, 215129, www.csisolar.com, support@csisolar.com