JTS260PP-60 245-260 Watt

Poly Crystalline Module

100% EL Inspection ensures Modules are defect free

Positive Power Tolerance- 0/+5W







Multicrystalline Modules Designed for Commercial and Solar Farm (grid-tied & off-grid), Industrial / Residential Rooftop Applications



Polycrystalline 60-cell Module achieves Power Output of up to 260Wp with 16.0% Conversion Efficiency



High Transmittance and Low Iron Tempered Glass with Anti-reflective Coating



Outstanding Performance in Low -light Irradiance environment



Excellent Mechanical Load Resistance which can withstand High Wind Loads (2400Pa) and Snow Loads (5400Pa)



High Salt Mist Corrosion Resistance



PID Resistant Modules with Long-term Reliability

We believe in a sustainable future, and we believe in creating it ourselves. Being a multi-product organisation and one of India's leading engineering companies, Jyotitech Group has dedicated itself to leaving behind a green legacy. Working for greater good, our eco-conscious values have driven us into delivering world-class solar energy products. Manufactured using state-of-the-art technology from Ecoprogetti, Italy, each Jyotitech Solar product is created with the single minded objective of reducing carbon footprints and global warming.

Headquartered in Navi Mumbai, India, the group has diverse ventures in manufacturing of enclosures, racks, LT / MV / HT electrical panels and bus bars besides solar products. We are committed to delighting our customers with best quality products and help them maximise their cost efficiency with clean energy. So come, join us and play a part in energising the future.



- 10 Years Limited product Warranty#
- 25 years Limited Power Output Warranty#
 - Minimum 90% at the end of 10 years
 - Minimum 80% at the end of 25 years



Certificates

Factory: ISO 9001:2008 ISO 14001:2004 BS OHSAS 18001:2007 Products: IEC 61215, IEC 61730 IEC 61701, IEC 62804 CE

| Electrical Characteristics* | | | | |
|--|---------------|---------|---------|---------|
| Model | JTS-245 | JTS-250 | JTS-255 | JTS-260 |
| | STC | STC | STC | STC |
| Nominal Maximum Power, $P_m(w)^*$ | 245Wp | 250Wp | 255Wp | 260Wp |
| Power Tolerance | | | | |
| Open Circuit Voltage, V _{oc} (V)* | 37 | 37.10 | 37.20 | 37.30 |
| Short Circuit Current, I _{sc} (A)* | 8.80 | 8.94 | 9.10 | 9.25 |
| Voltage at Maximum Power, V_{mp} (V)* | 30.70 | 30.80 | 30.90 | 31 |
| Current at Maximum Power, I _{mp} (A)* | 7.98 | 8.10 | 8.24 | 8.37 |
| Maximum System Voltage (V) | 1000VDC (IEC) | | | |
| Module Efficiency (%)* | 15.06 | 15.38 | 15.70 | 16 |
| Maximum Series Fuse Rating (A) | 15 | | | |
| Limiting Reverse Current (A) | | 15 | | |


*Standard Test Conditions (STC): 1000 W/m² irradiance, AM 1.5 spectrum and 25 Deg. C cell temperature.

Mechanical Characteristics*


Safety Class

Length X Width X Thickness (L x W x T) - mm: 1640 x 990 x 35 Weight (kg) 18.50 Solar Cells Per Module / Arrangement 60/(10*6) Solar Cell Type Multicrystalline Silicon / 156 x 156 Front Cover (Material / Thickness) Tempered & Low Iron Glass / 3.2 mm Encapsulate Ethylene Vinyl Acetate Anodized Aluminum Alloy Frame Material IP65 or IP67 Junction Box No. of Bypass Diodes : 3/6 MC4 Compatible Connector : 1000 mm / 4 mm² Cable Mechanical Load (Wind/Snow) 2400Pa / 5400Pa Fire Safety Class : C Safety Application Class : A

I-V Curve Variation with Irradiance



I-V Curve Variation with Temperature



*The specifications may change and Jyotitech Solar reserves the right to change them without prior notice, the rated electrical characteristics tolerance +/- 3%.

Conditions Apply.

Jyotitech GmbHHildesheimer Str. 265, 30519 Hannover Germany

Thermal Characteristics*

Temp. Coefficient of Current (I_{ec}), α (%/ $^{\circ}$ C) : 0.058


Temp. Coefficient of Voltage (V_{ec}), β (%/ $^{\circ}$ C) : -0.324

Temp. Coefficient of Power (P_m), γ (%/ $^{\circ}$ C) : -0.396

NOCT ($^{\circ}$ C) : 45 ± 2

Operating Temperature Range ($^{\circ}$ C) : -40 to 85

Module Dimension



Caution: Follow Installation and User Manual instructions carefully



Jyotitech Solar LLP

R-456, TTC Industrial Area, MIDC, Rabale, Navi Mumbai – 400701, India. Email: sales@jyotitechsolar.com | Tel: +91 22 27605000 / 27695000 www.jyotitechsolar.com