

MAX 98.1% EFFICIENCY

IP65 PROTECTION



 SAFE & RELIABLE

- High reliability due to good heat dissipation design
- Integrated lightning protection for both DC and AC
- Adapt to complex power grid
- High anti-corrosion ability with aluminum alloy die casting technology
- IP65, wider working temperature and altitude, adapt to various installation environments

 HIGH YIELD

- High yield with Max. 98.1% efficiency
- European weighted efficiency 97.5%
- Wide MPPT voltage range
- Up to 10% continuous output overloading capacity
- Dual MPPT design with precise MPPT algorithm

 EASY TO USE

- Compact elegant design, light weight, one-person installation
- Plug and play connectors, easy for installation
- Support wireless and wired internet connection (RS485 /WiFi/GPRS/LAN optional)
- Remote upgrading available
- Fast and easy configuration via App or OLED display

TECHNICAL PARAMETERS

SINGLE PHASE:RS-3KTL - 6KTL

Model	RS-3KTL	RS-3.6KTL	RS-4.2KTL	RS-4.6KTL	RS-5KTL	RS-6KTL
Input						
Max. Input Power (W)	4,800	5,760	6,720	7,360	8,000	9,600
Start-up Voltage (V)	80	80	80	80	80	80
Min. DC Voltage (V)	100	100	100	100	100	100
Max. DC Input Voltage (V)	600	600	600	600	600	600
Rated DC Input Voltage (V)	360	360	360	360	360	360
MPPT Voltage Range (V)	100-550	100-550	100-550	100-550	100-550	100-550
No. of MPP Trackers	2	2	2	2	2	2
No. of DC Inputs per MPPT	1/1	1/1	1/1	1/1	1/1	1/1
Max. Input Current (A)	15/15 [Ⓞ]	15/15 [Ⓞ]	15/15 [Ⓞ]	15/15 [Ⓞ]	15/15 [Ⓞ]	15/15 [Ⓞ]
Max. Short-circuit Current (A)	20/20	20/20	20/20	20/20	20/20	20/20
Output						
Rated Output Power (W)	3,000	3,600	4,200	4,600	5,000	6,000
Max. Output Power (W)	3,300	3,960	4,600	4,600	5,500 *	6,600
Max. Apparent Power (VA)	3,300	3,960	4,600	4,600	5,500 *	6,600
Rated Output Voltage (V)	220/230					
Rated AC Frequency (Hz)	50/60Hz 45-55Hz/55-65Hz					
Max. Output Current for each MPPT (A)	15	18	21	21	25 **	28.7
Power Factor	0.8 leading ...0.8 lagging					
Max. Total Harmonic Distortion	<3% @Rated Output Power					
DCI	<0.5%In					
Efficiency						
Max. Efficiency	98.1%	98.1%	98.1%	98.1%	98.1%	98.1%
European Efficiency	97.5%	97.5%	97.5%	97.5%	97.5%	97.5%
MPPT Efficiency	99.9%	99.9%	99.9%	99.9%	99.9%	99.9%
Protection						
DC Reverse Polarity Protection	Integrated					
Insulation Resistance Protection	Integrated					
DC Switch	Optional					
Surge Protection	Integrated					
Over-temperature Protection	Integrated					
Residual Current Protection	Integrated					
Islanding Protection	Integrated					
AC Short-circuit Protection	Integrated					
AC Over-voltage Protection	Integrated					
General Data						
Dimensions (mm)	410W*360H*120D					
Weight (kg)	13					
Protection Degree	IP65					
Self-consumption at Night (W)	<1					
Topology	Transformer less					
Operating Temperature Range (° C)	-30~60					
Relative Humidity (%)	0~100					
Operating Altitude (m)	4000 (derating@ > 3000)					
Cooling	Natural Convection					
Noise Level (dB)	< 25					
Display	OLED & LED					
Communication	RS485/WiFi/GPRS/LAN (Optional)					
Compliance	NB/T32004, IEC62109, IEC62116, VDE4105, VDE0126, UTE C15-712-1, AS4777, C10/11, CEI0-21, RD1699, NBR16149, IEC61727, IEC60068, IEC61683, EN50549, EN61000					

*: 5000 for Belgium. **: 21.7 for Belgium.