


SLP140-24C1D2

High Efficiency Multicrystalline PV Module


CSA® Certified to UL1703 and cUL1703
US Certified for Hazardous Environments
C1D2 - Class 1, Division 2

Electrical Characteristics	SLP140-24C1D2
Product code	140012464
Maximum power (Pmax)	140W
Voltage at Pmax (Vmp)	36.95V
Current at Pmax (Imp)	3.79A
Open-circuit voltage (Voc)	43.97V
Short-circuit current (Isc)	4.02A
Temperature coefficient of Voc	-(80±10)mV/°C
Temperature coefficient of Isc	(0.065±0.015)%/°C
Temperature coefficient of power	-(0.5±0.05)%/°C
NOCT (Air 20°C; Sun 0.8kW/m² wind 1m/s)	47±2°C
Operating temperature	-40°C to 85°C
Maximum system voltage	1000V DC
Power tolerance	± 5%


*STC: Irradiance 1000W/m², AM1.5 spectrum, module temperature 25°C
 *NOCT: Nominal operating cell temperature (the data is only for reference)




Module Diagram



Dimensions in brackets are in inches.
 Un-bracketed dimensions are in millimeters.
 Unit: mm[in.]



Junction Box
Top View (Lid Open)




Section A-A

Features

- Nominal 24V DC for standard output.
- Outstanding low-light performance.
- Heavy-duty anodized frames.
- High transparent low-iron, tempered glass.
- Rugged design to withstand high wind pressure, hail and snow load.
- Aesthetic appearance.

Characteristics



SLP140-24C1D2 I-V Curves

Specifications	SLP140-24C1D2
Cells	Polycrystalline silicon solar cell
No. of cells and connections	72(4X18)
Module dimension	1500mm[59.06in.],x675mm[26.57in.],x50mm[1.97in.]
Weight	12.0kg[26.46lbs]
Packing information(Carton)	1540mm[60.63in.],x715mm[28.15in.],x115mm[4.53in.]/(2pcs/ctn)

*Limited warranty: 5-year limited warranty of materials and workmanship; 10-year limited warranty of 90% power output; 25-year limited warranty of 80% power output. For detail, please contact us.
 *Specifications are subject to change without notice at any time.