

柜式储能电池/Cabinet Type Energy Storage Battery

SNU-48100- I



产品参数/Parameters

产品型号/Product model	SNU-48100- I
产品规格 / Product specification	48V100Ah
标称电压/Nominal voltage	48V
标称容量/Nominal capacity	100Ah
电芯类型/Cell type	磷酸铁锂(LFP)
标准充电电压/Standard charge voltage	54.75V
最大充电电流/Max discharge current	100A
放电截止电压/Discharge cut-off voltage	37.5V
最大放电电流/Max discharge current	100A
电量显示/Display	LCD(可选Optional)
通讯接口/Communication interface	RS485、RS232、CAN(可选Optional)
循环寿命/Cycle life	≥3000周(80%DOD)
充电温度范围/Charge temperature range	0~65°C
放电温度范围 /Discharge temperature range	-20~65°C
颜色/Colour	黑色(Black)
尺寸/Dimensions	442×430×178MM
重量/Weight	约47.5Kg
安装方式/Installation method	机柜式(Cabinet type)



比能量高
Higher specific energy



安装方便
Easy to install



循环寿命长
Long cycle life



支持并机使用
Support parallel operation



环保无污染
Environmental protection and no pollution



支持深度定制
Support deep customization

柜式储能电池/Cabinet Type Energy Storage Battery

SNU-48600- I



产品参数/Parameters

产品型号/Product model	SNU-48600- I
产品规格 / Product specification	48V600Ah
标称电压/Nominal voltage	48V
标称容量/Nominal capacity	600Ah
电芯类型/Cell type	磷酸铁锂(LFP)
标准充电电压/Standard charge voltage	54.75V
最大充电电流/Max discharge current	100A
放电截止电压/Discharge cut-off voltage	37.5V
最大放电电流/Max discharge current	100A
电量显示/Display	LCD(可选Optional)
通讯接口/Communication interface	RS485、RS232、CAN(可选Optional)
循环寿命/Cycle life	≥3000周(80%DOD)
充电温度范围/Charge temperature range	0~65°C
放电温度范围 /Discharge temperature range	-20~65°C
颜色/Colour	黑色(Black)
尺寸/Dimensions	600×600×1600MM
重量/Weight	约550Kg
安装方式/Installation method	机柜式(Cabinet type)



比能量高
Higher specific energy



安装方便
Easy to install



循环寿命长
Long cycle life



支持并机使用
Support parallel operation



环保无污染
Environmental protection and no pollution



支持深度定制
Support deep customization