



OPzV series is also kind of Valve Regulated Lead Acid battery which adopt immobilised Gel and Tubular Plate, offering high reliability & stable performance. With die-casted positive grid & patented active material formula, they offer 20+ years design life for float service @ 25°C and more suitable for cyclic use under extreme conditions.

Widely used for telecom, solar/photovoltaic/wind energy storage and UPS.

Model	Voltage (V)	Capacity (10HR/Ah)	Dimension (mm)				Weight (Kg)
			Length	Width	Height	Total Height	
OPzV2-100	2	100	103	206	355	399	12.0
OPzV2-150	2	150	103	206	355	399	15.5
OPzV2-200	2	200	103	206	355	399	18.0
OPzV2-250	2	250	124	206	355	399	21.0
OPzV2-300	2	300	145	206	355	399	25.0
OPzV2-350	2	350	124	206	471	512	27.0
OPzV2-420	2	420	145	206	471	512	32.0

Model	Voltage (V)	Capacity (10HR/Ah)	Dimension (mm)				Weight (Kg)
			Length	Width	Height	Total Height	
OPzV2-490	2	490	166	206	471	512	36.0
OPzV2-600	2	600	145	206	647	688	45.0
OPzV2-800	2	800	191	210	647	688	60.0
OPzV2-1000	2	1000	233	210	647	688	73.0
OPzV2-1200	2	1200	275	210	647	688	87.0
OPzV2-1500	2	1500	275	210	797	838	107.0
OPzV2-2000	2	2000	397	212	772	813	143.0
OPzV2-2500	2	2500	487	212	772	847	179.0
OPzV2-3000	2	3000	576	212	772	813	214.0