




MONOCRYSTALLINE PERC SOLAR MODULE SPE 395 / 400



Experience and Reliability

More than 200 years experience of Schmid & Pekintas Groups

Production With Full Automation

All processes that require high sensitivity are done with robotic systems in Schmid Pekintas high-tech production line. Full automation in Schmid Pekintas line enables production of high quality Photovoltaic (PV) modules as superior in performance, long life and durability. Schmid Pekintas offers high quality products to customers according to the international standards by using German Technology.

Positive Power Tolerance

Power output of Schmid Pekintas solar modules have always positive (+) tolerance. During production, all solar modules are automatically classified according to the power output values.

Excellent Resistance To Harsh Environment

Schmid Pekintas solar modules have high resistance to salt water and ammonia. Therefore, they can safely be used in corrosive environments such as animal farms and marine sites.



World Class Quality

High Product Quality | High Efficiency | Anti-PID technology | Positive Power Tolerance
0 / +5 Wp

Robust and Aesthetic Design | High Long-Term Performance | 25 years Linear Performance Guarantee
10 years Product Warranty

5400Pa Snow Load, **2400Pa** Wind Load Resistance | **1000V / 1500V** Maximum System Voltage



Electrical Characteristics (STC)

Model		SPE 395		SPE 400	
Maximum Power	P _{max}	395	Wp	400	Wp
Maximum Power Voltage	V _{mpp}	41.01	V	41.46	V
Maximum Power Current	I _{mpp}	9.64	A	9.66	A
Open Circuit Voltage	V _{oc}	49.08	V	49.33	V
Short Circuit Current	I _{sc}	10.20	A	10.22	A
Module Efficiency	η _m	19.85	%	20.10	%
Positive Power Tolerance		~ +5W			

Standard Test Conditions (STC) : Irradiance 1000 W/m², AM 1.5, Cell Temperature 25°C
Measurement Tolerance ± 3%.

Electrical Characteristics (NOCT)

Model		SPE 395		SPE 400	
Maximum Power	P _{max}	295	Wp	299	Wp
Maximum Power Voltage	V _{mpp}	38.05	V	38.40	V
Maximum Power Current	I _{mpp}	7.75	A	7.78	A
Open Circuit Voltage	V _{oc}	46.00	V	46.20	V
Short Circuit Current	I _{sc}	8.21	A	8.22	A

Nominal Operating Cell Temperature (NOCT) : Irradiance 800 W/m², AM 1.5, Wind Speed 1m/s.

System Design

Maximum System Voltage	1000 V DC (1500V DC upon request)
Operating Temperature	-40°C — +85°C
Maximum Series Fuse Rating	15 A
Static Load	5400 Pa
Safety Class	II
Fire Class	C

Thermal Characteristics


NOCT	45 ±2	°C
Temperature Coefficient P _{mp}	-0.377	% / °C
Temperature Coefficient I _{sc}	+0.029	% / °C
Temperature Coefficient V _{oc}	-0.272	% / °C

Mechanical Characteristics

Dimensions	1990mm x 1000mm x 35mm
Cell Type	Monocrystalline PERC, 158.75mm x 158.75mm
Cells per module	72
Weight	22kg ±1kg
Front Glass	3.2mm High transmission and tempered glass with low iron content
Encapsulation	EVA (Ethylene-Vinyl-Acetate)
Backsheet	PET film
Frame	Anodized aluminum alloy
J-Box	Protection class IP67 (3 bypass diode)
Cable	4 mm ² solar cable, Length: 1200mm
Connector	MC4 compatible


The information contained in this datasheet may deviate due to the ongoing innovation and product development processes. Schmid Pekintas reserves the right to make changes in the information described herein.

Module Technical Drawing




Performance at Low Irradiance


SPE 395 Current-Voltage Graph



SPE 395 Power-Voltage Graph



Warranty



10 years Product Warranty **25 years** Linear Performance Guarantee



Head Office

📍 Büyükdere Caddesi No:32 Pekintaş
İş Merkezi - 34388 Mecidiyeköy - İstanbul
☎ +90 (212) 267 00 61
📠 +90 (212) 288 60 44

Factory

📍 2.OSB 318. Ada 1. Parsel Cumhuriyet Mah.
1. Cd. No:5 - 81600 Beyköy - Düzce
☎ +90 (380) 790 01 55
📠 +90 (380) 790 01 56

