

#### **Specifications**

Model Type	AU115-18-M
Peak Power(Pmax)	115.00
Maximum Power Voltage(Vmp)	19.04
Maximum Power Current(Imp)	6.04
Open Circuit Voltage(Voc)	23.32
Short Circuit Current(Isc)	6.36
Cells Efficiency( %)	19.61
Module Efficiency( % )	16.96
Maximum System Voltage(V)	1000
Maximum Series Fuse Rating(A)	10
Power Tolerance	0 ~ +3 %
Pmax Temperature Coefficients(W/°C)	-0.400 %
Voc Temperature Coefficients(V/°C)	-0.290 %
Isc Temperature Coefficients(A/°C)	+0.048 %
NOCT Nominal Operating Cell Temperature(	45±2
Operating and Storage Temperature(°C)	-40 ~ +85
Standard Test Condition(STC)	1.000W/m²;AM 1.5;25+/-2°C

### **Key Features**



# 5 Busbar Cell:

5 Busbar Solar cell adpots new technology to improve the efficiency of modules,offers a better aesthetic apperance making it perfect for rooftop installation and application



### High Efficiency

High Module conversion efficiency, through innovative manufactureing technology



# Low-Light Performance

Advanced glass and solar cell surface texturing allow for excellent performance in low-light environments



# Serve Weather Resilience

Certified to withstand: wind load(2400Pa) and snow load (5400Pa)



# Durability against extreme enviromental conditions High salt mist and ammonia resistance certified by TUV




0-+5W Positive Tolerance Detailed information in Electrical Specifications

## Mechanical characterisrtics

Cell Type	Mono-crystalline 156.75×104.5mm
No. of Cells	36(4×9)
Dimensions	1015×668×30mm
Weight	8.0kgs
Front Glass	3.2mm high transmission, low iron, tempered glass
Frame	Anodized Aluminium Alloy
Junction box	IP65 Rated
Output cables	2.5mm <sup>2</sup> cable 90cm+mc4
Quantity/cartons	5pcs

Product Standard	
Product Performance	IEC61215
Product Safety	IEC61730

#### Linear Performance Warranty





Guarantee on product materail and workmanship



Linear Power output warranty

## Certification

**Drawing Picture** 



## 115W Mono solar panel (1015\*668\*30)

