

Tracer-AN Solar Charge Controller

60A, 12/24VDC Auto
50-100A, 12/24/36/48VDC Auto



Overview:

Tracer-AN (50A-100A) series is the largest charge controller series in EPEVER's product range and can take up to 5KW solar panel. For even more power, the user can use PAL-ADP-50N to connect max. 6 units of a controller in parallel for up to 30KW system. The multiple dry contact signals are designed for a diversified application.

Features:

- *MPPT tracking efficiency above 99.5%
- *Maximum charge conversion efficiency as high as 98%
- *Support lead-acid and lithium-ion batteries
- *Common negative grounding, Charging current up to 100A
- *Charging power and current limitation function
- *High-temperature charging power derating function
- *3 relays design for different demand: utility, generator and load
- *Support up to 6 units in parallel
- *Remote temperature and voltage sensor design
- *Isolated RS-485 with 5VDC/200mA and MODBUS protocol

Specifications

Model	Tracer6210AN	Tracer5415AN	Tracer6415AN	Tracer8415AN	Tracer10415AN	Tracer5420AN	Tracer6420AN	Tracer8420AN	Tracer10420AN
Nominal system voltage	12/24VDC/Auto	12/24/36/48VDC/Auto							
Battery type	Lead-acid (Sealed/Gel/Flooded)/Lithium (LiFePO ₄ /Li(NiCoMn)O ₂)/User								
Battery input voltage range	8V ~ 32V	8V ~ 68V	8V ~ 68V	8V ~ 68V	8V ~ 68V	8V ~ 68V	8V ~ 68V	8V ~ 68V	8V ~ 68V
Rated charge current	60A	50A	60A	80A	100A	50A	60A	80A	100A
Rated charge power	750W/12V 1500W/24V	625W/12V 1250W/24V 1875W/36V 2500W/48V	750W/12V 1500W/24V 2250W/36V 3000W/48V	1000W/12V 2000W/24V 3000W/36V 4000W/48V	1250W/12V 2500W/24V 3750W/36V 5000W/48V	625W/12V 1250W/24V 1875W/36V 2500W/48V	750W/12V 1500W/24V 2250W/36V 3000W/48V	1000W/12V 2000W/24V 3000W/36V 4000W/48V	1250W/12V 2500W/24V 3750W/36V 5000W/48V
Max. conversion efficiency	98.00%	98.30%	98.60%	98.50%	98.60%	98.30%	98.10%	98.50%	98.50%
Tracking efficiency	≥99.5%								
Max. PV open circuit voltage	100V(At minimum operating environment temperature) 92V (At 25°C environment temperature)	150V(At minimum operating environment temperature) 138V(At 25°C environment temperature)				200V (At minimum operating environment temperature) 180V(At 25°C environment temperature)			
MPP voltage range	(Battery Voltage +2V) ~ 72V	(Battery Voltage +2V) ~ 108V				(Battery Voltage +2V) ~ 144V			
Equalization voltage	Sealed:14.6V,Flooded:14.8V,User-defined:9-17V								
Boost voltage	Gel:14.2V,Sealed:14.4V,Flooded:14.6V,User-defined:9-17V								
Float voltage	Gel/Sealed/Flooded:13.8V,User-defined:9-17V								
Low voltage reconnect voltage	Gel/Sealed/Flooded:12.6V,User-defined:9-17V								
Low voltage disconnect voltage	Gel/Sealed/Flooded:11.1V,User-defined:9-17V								
Self-consumption	98mA/12V;60mA/24V;50mA/36V;46mA/48V								
Temperature compensation (for lead-acid battery)	-3mV/°C(2V(Default))								
Relative humidity	5% to 95% (N.C.)								
Enclosure	IP20								
Communication interface	RS485(5VDC/200mA, Two RJ45 ports in parallel)								
Grounding	Common negative								
Operating temperature range	-25°C ~ +60°C(derating above 45°C)								
Dimensions(LxWxH)(mm)	340×232×105.2	261×216×119	340×236×119	394×240×134	394×242×143	261×216×119	340×236×119	394×240×134	394×242×143
Net weight	3.5kg	3.5kg	4.5kg	6.1kg	7.4kg	3.5kg	4.5kg	6.1kg	7.4kg

1. The controller can't automatically identify system voltage if lithium batteries were connected.
2. The voltage point is for 12V system, please *2 in 24V system, *3 in 36V system, *4 in 48V system.

Accessories (optional)




MT-75
Remote Meter




MT-50
Remote Meter



EPEVER-RTU-4G
Wireless Data Transmission Unit



EPEVER-WIFI-2.4G-RJ45-A
WIFI Serial Server



EPEVER-BLE-RJ45-A
Bluetooth Module



PAL-ADP-50A
Parallel Adapter

EPEVER can provide many accessories to meet different applications. Please contact sales for more accessories information.