MONOCRYSTALLINE SOLAR PANEL TS-S140M





High conversion efficiency Extremely environmental testing Salt mist corrosion resistant Salt nist corrosion resistant P67 Junction box Strong compressive strength Fire test approved PID Resistant

GIVING YOU MORE



3% positive tolerance



Authorised photovoltaic certificates


P

Series of internal harsh tests



Linear performance warranty

Top Solar was established in 2008 and is a hi-tech corporation with its core business in R&D,manufacturing and sale of high efficiency solar panel.



Shenzhen Top Solar Energy Co., Ltd.

F4, Building C, Zhonghengxinda Industrial Park,

Shajing Town,Baoan District,Shenzhen City,Guangdong Province,China Tel:86 755 85224431 Fax:86 755 28167996 Email:info@topsolar-energy.com

www.topsolar-energy.com



Electrical Characteristics under STC*

Model No.:	TS-S140M	
Maximum Power-Pmax(Wp)	140W	
Voltage at Maximum Power-Vmp(V)	17.8V	
Current at Maximum Power-Imp(A)	7.87A	
Open Circuit Voltage-Voc(V)	21.7V	
Short Circuit Current-Isc(A)	8.6A	
Solar Panel Efficiency(%)	14.1	
Power Tolerance(%)	0/+3	

Mechanical Characteristics

Cell Type	Monocrystalline 156*156mm
Number of Cells	36(4*9)
Dimension	1380*670*35mm
Weight	11kg
Front Glass	Low Iron Tempered Glass
Encapsulant	EVA
Frame	Anodized Aluminum Alloy

Temperature Characteristics


NOCT*	45±2 ℃
Temperature Coefficient of Pmax(%)	−0.40/ °C
Temperature Coefficient of Voc(%)	–0.31/ °C
Temperature Coefficient of Isc(%)	0.04/°C


Maximum System Ratings

Operating Temperature	−40 °C to +85°C
Maximum System Voltage	1000V DC
Maximum Series Fuse Rating	15A

Warranty

- 12 years product warranty
- 12 years warranty on 90% power output
- 25 years warranty on 80% power output





1380 04

670

*STC(Standard Testing Conditions):Irradiance 1000W/m², cell temperature 25 °C, AM=1.5 *NOCT(Nominal Operating Cell Temperature):Irradiance 800W/m², ambient temperature 20 °C, wind speed 1m/s The specifications in this datasheet are subjected to change without prior notice