



IGNITE THE POWER OF NATURE

Monocrystalline Module --small size 160Watt

Model (RD160M6) Specifications



Electrical Data

Maximum Power(W)	160W
Optimum Power Voltage(Vmp)	18.75V
Optimum Operating Current(Imp)	8.53A
Open Circuit Voltage(Voc)	22.46V
Short Circuit Current(Isc)	8.83A
Cell Efficiency	19.12%
Module Efficiency	16.35%
Tolerance Wattage	0~+3%
NOCT	47°C +/-2°C

Benefits

- High efficiency solar cells with high transmission and textured glass are delivering high efficiency for modules;
- Bypass diode minimizes the power drop caused by shade;
- Tempered glass, EVA resin, and weatherproof film, plus aluminum frame for extended outdoor use;
- Modules independently tested to ensure conformance with certification and regulatory standards;
- Manufacturing facility certified to ISO 9001 quality management system standards.

Modules sorted by current, optimizing system power generation

High Efficiency

Stable Power <math><1\%</math>

Low Carbon Emission

Excellent Weather Resistance

Applications

- On-grid residential roof-tops
- On-grid commercial/industrial roof-tops
- Solar power stations
- Other on-grid applications

Temperature Coefficients

Temperature Coefficients of Isc(%)/°C	+0.04
Temperature Coefficients of Voc(%)/°C	-0.38
Temperature Coefficients of Pm(%)/°C	-0.47
Temperature Coefficients of Im(%)/°C	+0.04
Temperature Coefficients of Vm(%)/°C	-0.38





IGNITE THE POWER OF NATURE

Monocrystalline Module --small size 160Watt

Components & Mechanical

Solar Cell	156.75*156.75 Mono
Number of Cell(pcs)	4*9
Size of Module(mm)	1485*668*40
Front Glass Thikness(mm)	3.2
Surface Maximum Load Capacity	2400Pa
Allowable Hail Load	23m/s ,7.53g
Weight Per Piece(KG)	11.6
Bypass Diode Rating(A)	10
Frame(Material Corners,etc.)	40#
Temperature Range	-40°C to +85°C
FF (%)	70-76%
Standard Test Conditions	AM1.5 1000W/m ² 25°C

Warranty & Certifications

Warranty	25 years limited power warranty
	10 years limited product warranty
Certifications	IEC 61215, IEC 61730


Packing

Packing	2PCS/CTN or Pallet Packing
---------	----------------------------

Project Picture



Engineering Drawings



©2019 NINGBO RENELED NEW ENERGY CO.,LTD. All rights reserved.

Specifications included in this datasheet are subject to change without notice.

NINGBO RENELED NEW ENERGY CO.,LTD.

ADD: No. 35 Jintong Road, Binhai Industrial Park,

Xiangshan County, Ningbo, 315700, China

TEL: 0086 (0)574 65786319

FAX: 0086 (0)574 65786317

Email: info@renepv.com

