

# **S1-M 290-300** MODULE

Tolerance 0 ~ +0.2% - 290 Wp Tolerance 0 ~ -0.3% - 300 Wp

ISO9001:2015







# **KEY FEATURES**



#### 4 Busbar Solar Cell:

4 busbar solar cell adopts new technology to improve the efficiency of modules , offers a better aesthetic appearance, making it perfect for rooftop installation.



### High Efficiency:

Module efficiency up to 18.41%



#### Low-light Performance:

Advanced glass and solar cell surface texture allow for excellent performance in low-light environments. Generate energy even on cloudy days.



#### Durabitility

Long-lasting quality in any climate conditions



Made in Bahrain

# LINEAR PERFORMANCE WARRANTY



# Engineering Drawings

H±0.5

Side

1639±2

Π

Ш

## **Electrical Performance**

#### Current-Voltage Curves:



Front



40±2

100

Back

#### **Packaging Configuration**

( Two boxes=One pallet)

26pcs/box, 52pcs/pallet, 728 pcs/40'HQ Container

# **Mechanical and Physical Characteristics**

Module S1-290	S1-300
Cells 60 pcs; 156mm x 156mm; Monocrystalline 60 p	pcs; 156mm x 156mm; Monocrystalline
Weight 19.5 kg 19.5	5 kg
Dimensions L:1639mm W:991mm D:40mm to L:	.:1639mm W:991mm D:40mm
Glass 3.2mm Tempered, low-iron, ARC Glass 3.2m	mm Tempered, low-iron, ARC Glass
Frame 40mm Anodised Aluminium Alloy 40m	nm Anodised Aluminium Alloy
Cable SizeArea: 4mm² Length: 1mArea	a: 4mm² Length: 1m
Junction Box IP 67 with MC 4 Connection IP 67	57 with MC 4 Connection

#### **Electrical Characteristics**

Maximum Power (Pmax)	290 Wp	300 Wp
Power Output Tolerance (W)	+0.5 W, -0 W	-0.9 W , +0 W
Voltage at Pmax (V mp)	32.52 V	32.84 V
Current at Pmax (I mp)	8.931 A	9.107 A
Open-Circuit Voltage (Voc)	38.58 V	39.48 V
Short-Circuit Current (lsc)	9.443 A	9.595 A
Module Efficiency	17.30%	18.41%
Standard Test Conditions	Air Mass AM 1.5	Air Mass AM 1.5
	Irradiance 1000 W/m <sup>2</sup>	Irradiance 1000 W/m <sup>2</sup>
	Cell Temperature 25 °C	Cell Temperature 25 °C
Temperature Coefficient of Isc (%/C)	+0.046	+0.047
Temperature Coefficient of Voc (%/C)	-0.31	-0.32
Temperature Coefficient of Power (%/C)	-0.4	-0.4
Maximum Series Fuse Rating (A)	15 A	15 A
Maximum System Voltage (Vdc)	1000 V	1000 V
Operating Temperature (°C)	-40/85	-40/85
Number of Bypass Diodes	3	3