
## **POLYCRYSTALLINE SOLAR PANEL**


## **TS-S100P**






















# **GIVING YOU MORE**



3% positive tolerance



Authorised photovoltaic certificates




Series of internal harsh tests



Linear performance warranty

Top Solar was established in 2008 and is a hi-tech corporation with its core business in R&D,manufacturing and sale of high efficiency solar panel.



www.topsolar-energy.com

Shenzhen Top Solar Energy Co.,Ltd.
F4,Building C,Zhonghengxinda Industrial Park,
Shajing Town,Baoan District,Shenzhen City,Guangdong Province,China
Tel:86 755 85224431 Fax:86 755 28167996 Email:info@topsolar-energy.com



# POLYCRYSTALLINE SOLAR PANEL

TS-S100P

#### **Electrical Characteristics under STC\***

Model No.:	TS-S100P
Maximum Power-Pmax(Wp)	100W
Voltage at Maximum Power-Vmp(V)	18.5V
Current at Maximum Power-Imp(A)	5.43A
Open Circuit Voltage-Voc(V)	22.14V
Short Circuit Current-Isc(A)	5.78A
Solar Panel Efficiency(%)	13.4
Power Tolerance(%)	0/+3

#### **Mechanical Characteristics**

Wicefianteal Characteristics	
Cell Type	Polycrystalline 156*156mm
Number of Cells	36(4*9)
Dimension	1100*678*35mm
Weight	8.8kg
Front Glass	Low Iron Tempered Glass
Encapsulant	EVA
Frame	Anodized Aluminum Alloy

### **Temperature Characteristics**


NOCT*	<b>45±2</b> ℃
Temperature Coefficient of Pmax(%)	−0.40/°C
Temperature Coefficient of Voc(%)	<b>-0.31/</b> ℃
Temperature Coefficient of Isc(%)	<b>0.04/</b> ℃


#### **Maximum System Ratings**


Operating Temperature	<b>–</b> 40°C to +85°C
Maximum System Voltage	1000V DC
Maximum Series Fuse Rating	15A

#### Warranty

- 12 years product warranty
- 12 years warranty on 90% power output
- 25 years warranty on 80% power output







\*STC(Standard Testing Conditions):Irradiance  $1000W/m^2$ , cell temperature  $25^{\circ}C$ , AM=1.5 \*NOCT(Nominal Operating Cell Temperature):Irradiance  $800W/m^2$ , ambient temperature  $20^{\circ}C$ , wind speed 1m/s The specifications in this datasheet are subjected to change without prior notice