




Heliuss energy

HELIUS INVICTUS


HMF224M6

705W - 720W

30-year linear power output warranty



SUPERIOR WARRANTY



INMETRO, IEC 61215, IEC 61730, IEC TS 62804, IEC 61701
ISO 9001:2008 - ISO 14001:2004 - OSHAS 18001:2007



SUPERIOR QUALITY

With MBB technology and half cell design, Heliuss Energy panels reduce cover of cell by busbars and improve current collection ability on cloudy days.



HIGH EFFICIENCY AND POWER DENSITY

High conversion efficiency and up to 720 W on 3.34m² (21.55%). More gain power per square meter.



PERFORMANCE WARRANTY

With up to 30 years of solar generation, Heliuss Energy warranty can guarantee the longevity of your project.



LIGHT AND RELIABLE

Thicker frames to ensure module resilience. Modules could be applied under ammonia, salt mist, high temperature, high humidity condition.



FIRE-PROOF PERFORMANCE

Modules are approved and tested under IEC 61730 and Class C Fire Test.

WWW.HE-SOLAR.COM




Helius
energy

MECHANICAL CHARACTERISTICS


Dimensions	2428 x 1376 x 35mm
Solar Cells	224 Monocrystalline Cells
Weight	37.3 kg
Frame	Anodized Aluminium Alloy
Frontal Glass	3.2mm High Transmission, Low Iron Tempered
J-Box	IP68 / 3 bypass diodes
Cables	4mm / length 1200mm

TEMPERATURE CHARACTERISTICS

Temperature Coefficient I _{sc}	0.05% / °C
Temperature Coefficient V _{oc}	-0.26% / °C
Temperature Coefficient P _{max}	-0.34% / °C
Nominal Module Operating Temperature NMOT	41°C ± -3°C
Operational Temperature	-40°C a + 85°C




TECHNICAL DIMENSIONS (MM)



ELECTRICAL CHARACTERISTICS

HMF224M6	705HL	710HL	715HL	720HL
Maximum Power P _{Max} (W)	705	710	715	720
Maximum Power Voltage V _{mp} (V)	64.80	64.97	65.18	65.39
Maximum Power Current I _{mp} (A)	10.88	10.93	10.97	11.01
Open Circuit Voltage V _{oc} (V)	76.87	77.06	77.27	77.48
Short Circuit Current I _{sc} (A)	11.42	11.44	11.45	11.47
Module Efficiency	21.10%	21.25%	21.40%	21.55%
Maximum System Voltage	1500VCC			

Test Conditions: 1000W/m², 25°C, AM=1.5



PACKAGING CONFIGURATION

Modules per Container 40HQ	496 pcs
Pallets per Container 40HQ	16
Modules per Pallet	31
Pallet Dimensions	2508 x 1424 x 1125mm
Gross Weight per Pallet (kg)	1181

Helius Energy reserves the right to change data and specifications without notices. All rights are reserved to Helius Energy. For more Informations, contact a technical representative or www.he-solar.com

JANUARY 2022

