


Mono-Crystalline Solar PV Module 36 Cells Series



Electrical Characteristics							
Specification	FX-110M	FX-115M	FX-120M	FX-125M	FX-130M	FX-135M	FX-140M
Rating power at STC (Wp)	110W	115W	120W	125W	130W	135W	140W
Open circuit voltage (Voc)	22.1V	22.2V	22.4V	22.6V	22.8V	23.0V	23.1V
Short circuit current (Isc)	6.96A	7.18A	7.42A	7.67A	7.73A	7.83A	7.88A
Rated voltage (Vm)	17.52V	17.61V	17.70V	17.78V	17.86V	17.93V	17.99V
Rated current (Im)	6.28A	6.53A	6.78A	7.03A	7.28A	7.53A	7.78A
Module efficiency (%)	13.13%	13.73%	14.32%	14.93%	15.52%	16.12%	16.72%
Power tolerance	0 - 3 % (W)						
Temperature coefficient of Pm	-0.45%/K						
Temperature coefficient of Isc	+0.052%/K						
Temperature coefficient of Voc	-0.33%/K						
Maximum system voltage	DC600v (UL) / DC1000V (IEC)						

All technical data at STC: AM1.5; 1000W/m²; 25°C



Mechanical Characteristics	
Solar Cell	Monocrystalline
No. of cells	36 (4X9)
Nominal Operating Cell Temperature (NOCT)	46 ± 2 °C
Operation temperature	From -40 to +85°C
Typical Application	12V DC
Max series fuse rating	10A
Max wind resistance	2400Pa
Surface max. load capacity	5400Pa
Weight	9.5kg
Dimension	1250X670X35MM

Performance

- Water resistant junction box with bypass diode and high strength polymer sheet on module's rear ensures module is sealed from moisture and mechanical damage
- High transmissivity low-iron toughened glass
- Excellent weak light performance
- Unique drainage hole design and anodized aluminum frame

Quality and Reliability

- Superior reliability with guaranteed 0~3% power output tolerance
- 10 years warranty on materials and workmanship,
- 25 years linear power warranty, 97% in the first year, 91% in 10th year, and ending with 80% in 25th year
- Cells are individually tested, characterized and modulated prior to interconnection
- Test and produce standard: IEC61215, IEC61730, ISO 9001:2008, ISO14001:2004, OHSAS18001:2007, TIS18001:2011, TIS1843:2553, TIS2580:2555



1. Tempered glass
2. EVA
3. Cells
4. EVA
5. Back sheet