

HALF
CUT

320W-335W

144 efficient polycrystalline silicon cell modules

SLP320-24D SLP325-24D SLP330-24D SLP335-24D

Electric Performance Parameters

TYPE	SLP320-24D	SLP325-24D	SLP330-24D	SLP335-24D
Rated power (W)	320W	325W	330W	335W
Deviation of rated power (W)	0~+5W	0~+5W	0~+5W	0~+5W
Optimum operating voltage (Vmp)	36.91V	37.15V	37.45V	37.66V
Optimum operating current (Imp)	8.67A	8.75A	8.82A	8.90A
Open-circuit voltage (Voc)	44.62V	44.91V	45.28V	45.53V
Short-circuit current (Isc)	9.17A	9.26A	9.33A	9.42A
Temperature coefficient of open-circuit voltage	-0.32%/°C			
Temperature coefficient of short-circuit current	+0.06%/°C			
Temperature coefficient of rated power	-0.38%/°C			
Standard operating temperature	45±2°C			

STC: illumination intensity: 1000W/M², battery temperature: 25°C, air quality=1.5

NOCT: illumination intensity: 800W/M², environmental temperature: 20°C, air quality=1.5, wind speed: 1m/s

Packaging Information

Type of Cell	Polycrystalline silicon cell (156.75x78.375)
Cell Array	144(6x24)
Module Dimension	1988mm x 992mm x 40mm
Weight	22.3kg
Pallet Dimension	2036mm x1120mm x 1130mm(26 pieces/pallet)
Container loading information (40HQ)	572 pieces

Operation Condition

Maximum system voltage	1000V
Rated current of serial fuse	15A
Maximum front load	5400Pa (112 lb/ft ²)
Maximum back load	2400Pa (50 lb/ft ²)
Operating temperature range	-40~+85°C
Module Standard	A

Module Dimension: (unit: mm)

