



P30 SERIES

C-SI PV MODULE

OLI


245/250/255/

260/265

P30



Efficient at Low Light.



Withstands wind load of 2400 Pa.



Positive Power Tolerance.



IP67 Protection Junction Box.



All climate conditions.



**10 years, Product Guarantee.
25 Years Performance
Warranty.**

Due to continuous improvement in the product the specification may change without notice. However one can visit www.olitec.in for updated module specification and manual for the product.

Made In India

Electrical Data*

Model	OLI245 P30	OLI250 P30	OLI255 P30	OLI260 P30	OLI265 P30
Maximum Rating Power	245 W	250 W	255 W	260 W	265 W
Module Efficiency	14.87 %	15.19 %	15.46 %	15.78 %	16.09 %
Open Circuit Volatage (Voc)	37.62 V	38.0 V	38.2 V	38.4 V	38.6 V
Maximum Power Voltage (Vmp)	30.14 V	30.64 V	30.78 V	31 V	31.2 V
Short Circuit Current (Isc)	8.67 A	8.72 A	8.81 A	8.92 A	8.98 A
Maximum Power Current (Imp)	8.12 A	8.16 A	8.27 A	8.38 A	8.49 A

* At STC (Standard Test Condition), 1000W/m² AM 1.5, 25°C.

Cell Temperature Coefficients

Temperature Coefficient of Isc	0.045%/°C
Temperature Coefficient of Voc	-0.31%/°C
Temperature Coefficient of Pmax	-0.42%/°C

Physical / Mechanical Properties

Dimension	1661 x 991 x 35mm
Weight (approx.)	18 Kgs
No of Cells	60
Junction Box	IP67, 3 Bypass diode
Cable/Connectors	4mm ² , MC4/MC4
Frame	Anodized Aluminum
Glass	3.2 mm High transmission, Low iron tempered

Maximum Rating

Operational temperature	-40 ~ +85°C
Maximum system voltage	1000 VDC
Max series fuse rating	15 A

Certifications

IEC 61215, IEC 61730-1,-2, IEC 61701 Ed.2

