

Introduction

This time-tested legacy module series has been proven to be one of the powerful and most reliable products offered by BR Solar and the most popular choice by PV system installers and customers around world.



Low cost



12 busbar solar cell design




Anti-PID



Highly reliable due to strict quality control

Superior Warranty

- 10-year product warranty
- 25-year linear power output




■ Linear Power Warranty ■ Industry Warranty

Comprehensive Certificates

- IEC 61215, IEC 61730
- ISO 9001: 2015 Quality management systems
- ISO 14001: 2015 Environmental management systems
- ISO 45001: 2018 Occupational health and safety management systems
- IEC TS 62941: 2016 Terrestrial photovoltaic (PV) modules – Guidelines for increased confidence in PV module design qualification and type approval



MECHANICAL DIAGRAMS



SPECIFICATIONS

Cell	PERC
Weight	31.0kg
Dimensions	2172×1303×35mm
Cable Cross Section Size	4mm ² , 300mm
No. of cells	120(2x(6x10))
Junction Box	IP68, 3 diodes
Connector	1500V, MC4
Packaging Configuration	31 Per Pallet
Container	558pcs /40' HQ

Remark: customized frame color and cable length available upon request

ELECTRICAL PARAMETERS AT STC

TYPE	BR-M580W	BR-M585W	BR-M590W	BR-M595W	BR-M600W
Rated Maximum Power(Pmax) [W]	580	585	590	595	600
Open Circuit Voltage(Voc) [V]	41.1	41.3	41.5	41.7	41.9
Maximum Power Voltage(Vmp) [V]	33.8	34.0	34.2	34.4	34.6
Short Circuit Current(Isc) [A]	18.13	18.18	18.22	18.27	18.31
Maximum Power Current(Imp) [A]	17.16	17.21	17.26	17.30	17.35
Module Efficiency [%]	20.5	20.7	20.8	21.0	21.2
Power Tolerance	0~+5W				
Temperature Coefficient of Isc(α_{Isc})	+0.05%/°C				
Temperature Coefficient of Voc(β_{Voc})	-0.27%/°C				
Temperature Coefficient of Pmax(γ_{Pmp})	-0.35%/°C				
STC	Irradiance 1000W/m ² , cell temperature 25°C, AM1.5G				

Remark: Electrical data in this catalog do not refer to a single module and they are not part of the offer.They only serve for comparison among different module types.

ELECTRICAL PARAMETERS AT NOCT

TYPE	BR-M580	BR-M585	BR-M590	BR-M595	BR-M600
Rated Max Power(Pmax) [W]	438	441	445	449	453
Open Circuit Voltage(Voc) [V]	38.7	38.9	39.1	39.2	39.4
Max Power Voltage(Vmp) [V]	31.7	31.9	32.0	32.2	32.4
Short Circuit Current(Isc) [A]	14.59	14.63	14.66	14.70	14.73
Max Power Current(Imp) [A]	13.81	13.86	13.89	13.94	13.97
NOCT	Irradiance 800W/m ² , ambient temperature 20°C, wind speed 1m/s, AM1.5G				

OPERATING CONDITIONS

Maximum System Voltage	1500V DC(IEC)
Operating Temperature	-40°C~+85°C
Maximum Series Fuse	30A
Maximum Static Load,Front	5400Pa
Maximum Static Load,Back	2400Pa
NOCT	45±2°C
Application Class	Class A

CHARACTERISTICS

I-V/P-V Curve at Different Irradiance(600W)

