

Q.PEAK DUO XL-G11.7

570-590

EXCELLENT RELIABILITY
AND OUTSTANDING YIELDS



BREAKING THE 21% EFFICIENCY BARRIER

PERC Technology with zero gap cell layout boosts module efficiency up to 21.7%.



LOW ELECTRICITY GENERATION COSTS

Higher yield per surface area, lower BOS costs and up to 175 watts more module power than standard 144 half-cell modules.



ENDURING HIGH PERFORMANCE

Long-term yield security thanks to regular PID and Hot-Spot tests according to IEC requirements.



EXTREME WEATHER RATING

High-tech aluminium alloy frame, certified for high snow (5400 Pa) and wind loads (2400 Pa).



A RELIABLE INVESTMENT

Inclusive 12-year product warranty and 25-year linear performance warranty¹.

¹ See data sheet on rear for further information.

THE IDEAL SOLUTION FOR:




Ground-mounted
solar power plants

Engineered in Germany

Q CELLS

MECHANICAL SPECIFICATION

Format	2416 mm × 1134 mm × 35 mm (including frame)
Weight	30.7 kg
Front Cover	3.2 mm thermally pre-stressed glass with anti-reflection technology
Back Cover	Composite film
Frame	Anodised aluminium
Cell	6 × 26 monocrystalline PERC solar half cells
Junction box	53-101 mm × 32-60 mm × 15-18 mm Protection class IP67, with bypass diodes
Cable	4 mm ² Solar cable; (+) ≥ 750 mm, (-) ≥ 350 mm
Connector	Stäubli MC4-Evo2, Hanwha Q CELLS HQC4; IP68




Drawing not to scale

ELECTRICAL CHARACTERISTICS

POWER CLASS				570	575	580	585	590
MINIMUM PERFORMANCE AT STANDARD TEST CONDITIONS, STC ¹ (POWER TOLERANCE +5 W / −0 W)								
Minimum	Power at MPP ¹	P _{MPP}	[W]	570	575	580	585	590
	Short Circuit Current ¹	I _{SC}	[A]	13.49	13.51	13.54	13.57	13.59
	Open Circuit Voltage ¹	V _{OC}	[V]	53.59	53.62	53.64	53.67	53.70
	Current at MPP	I _{MPP}	[A]	12.82	12.87	12.92	12.97	13.01
	Voltage at MPP	V _{MPP}	[V]	44.46	44.68	44.90	45.12	45.33
	Efficiency ¹	η	[%]	≥ 20.8	≥ 21.0	≥ 21.2	≥ 21.4	≥ 21.5
MINIMUM PERFORMANCE AT NORMAL OPERATING CONDITIONS, NMOT ²								
Minimum	Power at MPP	P _{MPP}	[W]	427.6	431.4	435.1	438.9	442.6
	Short Circuit Current	I _{SC}	[A]	10.87	10.89	10.91	10.93	10.95
	Open Circuit Voltage	V _{OC}	[V]	50.54	50.56	50.59	50.62	50.64
	Current at MPP	I _{MPP}	[A]	10.09	10.13	10.17	10.22	10.26
	Voltage at MPP	V _{MPP}	[V]	42.39	42.58	42.77	42.96	43.14

¹Measurement tolerances P_{MPP} ± 3%; I_{SC}; V_{OC} ± 5% at STC: 1000 W/m², 25 ± 2°C, AM 1.5 according to IEC 60904-3 • ²800 W/m², NMOT, spectrum AM 1.5


Q CELLS PERFORMANCE WARRANTY



At least 98% of nominal power during first year. Thereafter max. 0.5% degradation per year. At least 93.5% of nominal power up to 10 years. At least 86% of nominal power up to 25 years.

All data within measurement tolerances. Full warranties in accordance with the warranty terms of the Q CELLS sales organisation of your respective country.

PERFORMANCE AT LOW IRRADIANCE



Typical module performance under low irradiance conditions in comparison to STC conditions (25°C, 1000 W/m²).

TEMPERATURE COEFFICIENTS

Temperature Coefficient of I _{SC}	α	[%/K]	+0.04	Temperature Coefficient of V _{OC}	β	[%/K]	-0.27
Temperature Coefficient of P _{MPP}	γ	[%/K]	-0.34	Nominal Module Operating Temperature	NMOT	[°C]	43 ± 3

PROPERTIES FOR SYSTEM DESIGN

Maximum System Voltage	V _{sys}	[V]	1500	PV module classification	Class II
Maximum Reverse Current	I _R	[A]	25	Fire Rating	C
Max. Design Load, Push/Pull		[Pa]	3600/1600	Permitted Module Temperature on Continuous Duty	-40°C - +85°C
Max. Test Load, Push/Pull		[Pa]	5400/2400		

QUALIFICATIONS AND CERTIFICATES

IEC 61215:2016, IEC 61730:2016.
This data sheet complies with DIN EN 50380.



PACKAGING INFORMATION



Vertical packaging

2458mm

1134mm

1270mm

1000kg

20 pallets

16 pallets

31 modules

Note: Installation instructions must be followed. See the installation and operating manual or contact our technical service department for further information on approved installation and use of this product.

Hanwha Q CELLS GmbH

Sonnenallee 17-21, 06766 Bitterfeld-Wolfen, Germany | **TEL** +49 (0)3494 66 99-23444 | **FAX** +49 (0)3494 66 99-23000 | **EMAIL** sales@q-cells.com | **WEB** www.q-cells.com

Engineered in Germany

Q CELLS