



RT-340 | 345 | 350 | 355P

Runtech Solar's modules use the latest innovative cell technology, increasing module power output and system reliability, ensured by 15 years of experience in module manufacturing, well-engineered module design, stringent BOM quality testing, an automated manufacturing process and 100% EL testing.

KEY FEATURES



Excellent module efficiency of up to 18.00 %



Cell efficiency of up to 20.0 %



Outstanding low irradiance performance: 96.5 %



High PTC rating of up to 92.21 %



IP67 junction box for long-term weather endurance



Heavy snow load up to 5400 Pa, wind load up to 2400 Pa



linear power output warranty



product warranty on materials and workmanship

MANAGEMENT SYSTEM CERTIFICATES*

ISO 9001:2008 / Quality management system

ISO/TS 16949:2009 / The automotive industry quality management system

ISO 14001:2004 / Standards for environmental management system

OHSAS 18001:2007 / International standards for occupational health & safety

PRODUCT CERTIFICATES*

IEC 61215 / IEC 61730: VDE / CE


UL 1703: CSA / IEC 61701 ED2: VDE / IEC 62716: VDE / Take-e-way



* As there are different certification requirements in different markets, please contact your local Runtech Solar sales representative for the specific certificates applicable to the products in the region in which the products are to be used.

Runtech CHINA COMPANY is committed to providing high quality solar products, solar system solutions and services to customers around the world. As a leading PV project developer and manufacturer of solar modules with over 0.5 GW deployed around the world since 2008, Runtech China Company is one of the most popular solar companies worldwide.

ENGINEERING DRAWING (mm)



ELECTRICAL DATA / STC*

RT	340M	345M	350M	355M
Nominal Max. Power (Pmax)	340 W	345 W	350 W	355 W
Opt. Operating Voltage (Vmp)	37.6 V	37.8 V	38.1 V	38.9 V
Opt. Operating Current (Imp)	9.05 A	9.13 A	9.21 A	9.30 A
Open Circuit Voltage (Voc)	45.9 V	46.0 V	46.2 V	46.5 V
Short Circuit Current (Isc)	9.62 A	9.69 A	9.79 A	9.84 A
Module Efficiency	17.49%	17.70%	18.03%	18.49%
Operating Temperature	-40°C ~ +85°C			
Max. System Voltage	1000 V (IEC) or 1000 V (UL)			
Module Fire Performance	TYPE 1 (UL 1703) or CLASS C (IEC 61730)			
Max. Series Fuse Rating	15 A			
Application Classification	Class A			
Power Tolerance	0 ~ + 5 W			

* Under Standard Test Conditions (STC) of irradiance of 1000 W/m², spectrum AM 1.5 and cell temperature of 25°C.

ELECTRICAL DATA / NOCT*

RT	340M	345M	350M	355M
Nominal Max. Power (Pmax)	251 W	254 W	258 W	262 W
Opt. Operating Voltage (Vmp)	36.4 V	34.8 V	35.1 V	35.6 V
Opt. Operating Current (Imp)	7.25 A	7.32 A	7.36 A	7.42 A
Open Circuit Voltage (Voc)	42.9 V	43.1 V	42.2V	42.4 V
Short Circuit Current (Isc)	7.76 A	7.82 A	7.90 A	7.98 A

* Under Nominal Operating Cell Temperature (NOCT), irradiance of 800 W/m², spectrum AM 1.5, ambient temperature 20°C, wind speed 1 m/s.


PERFORMANCE AT LOW IRRADIANCE

Outstanding performance at low irradiance, average relative efficiency of 96.0 % from an irradiance of 1000 W/m² to 200 W/m² (AM 1.5, 25°C).

The specification and key features described in this datasheet may deviate slightly and are not guaranteed. Due to on-going innovation, research and product enhancement, Runtech China Company. reserves the right to make any adjustment to the information described herein at any time without notice. Please always obtain the most recent version of the datasheet which shall be duly incorporated into the binding contract made by the parties governing all transactions related to the purchase and sale of the products described herein.

Caution: For professional use only. The installation and handling of PV modules requires professional skills and should only be performed by qualified professionals. Please read the safety and installation instructions before using the modules.

RT-335P / I-V CURVES



MECHANICAL DATA

Specification	Data
Cell Type	Poly-crystalline, 6 inch
Cell Arrangement	144 (6x12 x 2)
Dimensions	1960×992×35mm (77.2×39.1×1.57 in)
Weight	22.4 kg (49.4 lbs)
Front Cover	3.2 mm tempered glass
Frame Material	Anodized aluminium alloy
J-Box	IP67, 3 diodes
Cable	4 mm ² (IEC) or 4 mm ² & 12 AWG 1000V (UL), 1160 mm (45.7 in)
Connector	T4-1000V or PV2 series
Per Pallet	35 pieces
Per container (40' HQ)	840 pieces

TEMPERATURE CHARACTERISTICS

Specification	Data
Temperature Coefficient (Pmax)	-0.41 % / °C
Temperature Coefficient (Voc)	-0.31 % / °C
Temperature Coefficient (Isc)	0.053 % / °C
Nominal Operating Cell Temperature	45±2 °C

PARTNER SECTION

