





As the leading vertically integrated manufacturer of lithium iron phosphate battery systems, GSL ENERGY has provided various battery solutions for nearly all kinds of ESS applications. Thanks to our self-developed core technology in cells/BMS/system design, GSL ENERGY has delivered more than 138+ countries serving 100,000+ users.

www.gsl-energy.com

Long life and safety

Vertical industry integration ensures more than 6500 times cycles with 80% DoD.

Safe Lithium iron phosphate battery cell.

Intelligent

Each battery with independent BMS system manages power output smartly and effectively.

Modularization

Modular design gives the end customers the power of choice of capacity Deliver up to 163.8KW with single max module (10.24KWh) at 16pcs parallel connection.

Easy to install and use

Just plug and play to minimize the installation time and cost. Compact and fashionable design fits in your sweet home environment.

Compatiblity

Compatible with most of the available Hybrid inverters.

Safety Cert

IEC62619, UN38.3, ROHS, CE-EMC



| Battery Specifications | | |
|-----------------------------|--|--------------------|
| Model No | GSL 5000U - 5KWH | GSL 10000U - 10KWH |
| Nominal Parameters | | |
| Voltage | 51.2V | |
| Capacity | 100Ah | 200Ah |
| Energy | 5.12KwH | 10.24KwH |
| Dimensions (L x W x H) | 580x390x200mm | 685x435x231mm |
| Weight | 65kg | 100.5kg |
| Basic Parameters | | |
| Life Time(25°C) | 15 years | |
| Life Cycles(80% DOD, 25°C) | 6500Cycles | |
| Storage Time / Temperature | 5 months @ 25°C; 3 months @ 35°C; 1 month @ 45°C | |
| Operation Temperature | -20°C to 60°C @60+/-25% Relative Humidity | |
| Storage Temperature | 0°C to 45°C @60+/-25% Relative Humidity | |
| Lithium Battery Standard | IEC62619,UN38.3,ROHS,CE-EMC | |
| Enclosure Protection Rating | IP54 (Indoor use) | |
| Electrical Parameters | | |
| Operation Voltage | 46-56 Vdc | |
| Max.Charging Voltage | 56 Vdc | |
| Max.Charging Current | 100A (5120W) | |
| Max.Discharging Current | 150A (7680W) | |



