

O nly focus on portable solar since 2013

Tel.:+86-755-29420722 WeChat: 13828458256 simon@eyongpv.com

Engineering * Manufacturer * Exporter http://www.eyongpv.com

200W Foldable solar charger

High efficiency SunPower 200W ,fabric folding solar panel

We can do different plug according to customer requested

Light weight, portable to take out.

Temperature Coefficient of Isc:

Model No : EYP200F-34SP

Model No : EYP200F-34SP		
Product specification		
Bag material	600D	
Bag color	Black or camouflage color	
Open size	1550*830mm	
Folding size	425*290mm	
Foldinjg thickness	35mm	
No. of folding	10 = 2 * 5	
Net weight	7.25 KG	
Solar panel		
Solar Cell	Sunpower	
Efficiency rate	Above 22%	
Each Solar panel size	274*401*2.5mm	
Maximum power(Pm)	200W	
Power Tolerance	-5%	
Voltage at max power(Vmp)	34V	
Current at max power(Imp)	5.88A	
Open circuit voltage(Voc)	40.8V	
Short circuit current(Isc)	6.45A	
Operating Temperature	- 20°C −+60°C	
Maximum System Voltage	1000V DC	
Maximum Series Fuse Rating	10A	
Other functions or accessories	MC4 connector output	
Certifications	CE、FCC、ROHS	
Standard Test Condtion	Irrandiance 1000W/m² Module temperature 25°C,AM=1.5	
Guarantee product material and pro	ocess in a year	
Temperature Characteristics		
Noct :46°C ± 2°C		
Temperature Coefficient of Pmax:	(-0.41% /ºC)	
Temperature Coefficient of Voc:	(-0.33% /ºC)	

(+0.06% /ºC)

$\mathbf{p}_{\mathbf{r}}$	luct p	
THE R O A S	1 1 7 7 7	







