



SLP335S-24D SLP340S-24D SLP345S-24D SLP350S-24D

Electric Performance Parameters

TYPE	SLP335S-24D	SLP340S-24D	SLP345S-24D	SLP350S-24D
Rated power (W)	335W	340W	345W	350W
Deviation of rated power (W)	0~+5W	0~+5W	0~+5W	0~+5W
Optimum operating voltage (Vmp)	37.69V	37.78V	38.00V	38.26V
Optimum operating current (Imp)	8.89A	9.00A	9.08A	9.15A
Open-circuit voltage (Voc)	45.94V	46.05V	46.32V	46.64V
Short-circuit current (Isc)	9.33A	9.45A	9.53A	9.61A
Temperature coefficient of open-circuit voltage	-0.36%/°C			
Temperature coefficient of short-circuit current	+0.07%/°C			
Temperature coefficient of rated power	-0.38%/°C			
Standard operating temperature	45±2°C			

STC: illumination intensity: 1000W/M², battery temperature: 25°C, air quality=1.5

NOCT: illumination intensity: 800W/M², environmental temperature: 20°C, air quality=1.5, wind speed: 1m/s

Packaging Information

Type of Cell	Monocrystalline silicon cell (156.75x78.375)
Cell Array	144 (6x24)
Module Dimension	1988mm x 992mm x 40mm
Weight	22.3kg
Pallet Dimension	2036mm x 1120mm x 1130mm(26 pieces/pallet)
Container loading information (40HQ)	572 pieces

Operation Condition

Maximum system voltage	1000V
Rated current of serial fuse	15A
Maximum front load	5400Pa (112 lb/ft ²)
Maximum back load	2400Pa (50 lb/ft ²)
Operating temperature range	-40~+85°C
Module Standard	A

Module Dimension: (unit: mm)

