

Front Terminal Series Battery

Key Features:

- Strong heat dissipation and wide operating temperature range
- Avoid acid mist being separated out, environment friendliness
- Slim shape design and front terminal connection
- Prominent high rate discharge performance
- Optional fire retardant design
- Long designed service life
- Excellent discharge performance
- Environment friendliness



Applications:

- Solar and wind energy storage system
- EPS and UPS battery backup
- Telecommunication equipment
- Power plant and transmission system
- Great for power supply system of private network or LAN
- Signal system, emergency lighting system, security system

AGM Series

| Model | Voltage(V) | Capacity(Ah) | Weight(KG) | Dimension(MM) | | | | Terminal |
|----------|------------|--------------|------------|---------------|-------|--------|--------------|----------|
| | | | | Length | Width | Height | Total Height | |
| FT12V100 | 12 | 100 | 31 | 409 | 110 | 295 | 295 | M8 |
| FT12V150 | 12 | 150 | 41 | 551 | 110 | 288 | 288 | M8 |
| FT12V180 | 12 | 180 | 54 | 560 | 125 | 316 | 316 | M8 |

GEL Series

| Model | Voltage(V) | Capacity(Ah) | Weight(KG) | Dimension(MM) | | | | Terminal |
|-----------|------------|--------------|------------|---------------|-------|--------|--------------|----------|
| | | | | Length | Width | Height | Total Height | |
| GFT12V100 | 12 | 100 | 31 | 409 | 110 | 295 | 295 | M8 |
| GFT12V150 | 12 | 150 | 41 | 551 | 110 | 288 | 288 | M8 |
| GFT12V180 | 12 | 180 | 54 | 560 | 125 | 316 | 316 | M8 |