



Lithium Battery Energy Storage

EOS Series

SR-EOS10B













Lithium Battery Energy Storage

Intelligent

- Equipped with WIFI and Bluetooth communication, it supports Tuya cloud platform and can view battery information remotely.
- LCD touchscreen for easy viewing the battery information

Use Long life and safety

- High quality LiFePo4 long life span and high safety.
- IP65 waterproof rating, can be used in harsh environment

Easy to install and use

- Support 2 sets of battery interface, easy for different wiring methods
- Support wall-mounted and floor-mounted installation

Scalability

- Support USB interface, can communicate directly with computer, easy for parameter change and troubleshooting
- Support up to 9 batteries in parallel, and can form a maximum power system of 90kwh

SRNE

Compatiblity

Support various brands of inverter communication protocols











| MODEL | SR-EOS10B |
|---------------------------------|---|
| BATTERY | |
| Rated voltage | 51.2V |
| Rated capacity | 200Ah |
| Rated energy | 10.24kWh |
| Battery type | LFP |
| Life time(25°C) | 20 Years |
| Life cycles (80% DOD,0.5C,25°C) | 6000 Cycles |
| Max.charging voltage | 57.6V |
| Over discharge voltage | 44.8V |
| Max. charging current | 150A |
| Max. discharging current | 200A |
| Peak charging current | 200A (3S) |
| Peak discharging current | 220A (3S) |
| Max.Number of parallel | 9 |
| COMMUNICATION | |
| Communication interfaces | CAN/RS485/USB/WIFI/Bluetooth |
| GENERAL | |
| Storage time / temperature | 6 months @25°C;3 months @35°C;1 months @45°C; |
| Charging temperature range | 0~45°C (32~113°F) |
| Discharging temperature range | -10~45°C (14~113°F) |
| Cooling method | Natural cooling |
| Enclosure protection rating | IP65 |
| Weight | 88kg, (194lb) |
| Dimentions (L*W*H) | 1014*620*191mm(3*2*0.6ft) |
| CERTIFICATION | |
| Li-ion battery | UN38.3,MSDS,EN55032,EN55024, EN61000-3-2,EN61000-3-3 |

Details >>>







