

SNE-5KWh- I



逆变器参数/Inverter parameters

额定功率/Rated power	3KW
峰值功率/Peak power	5KW
输出波形/Output waveform	纯正弦波(Pure sine wave)
输入/输出交流电压/Input/Output AC voltage	110Vac/220Vac
输入/输出交流电压频率/Input/Output AC voltage frequency	50Hz/60Hz
逆变器类型/Type of inverter	高频(High frequency)

电池参数/Battery parameters

标称电压/Nominal voltage	51.2V
标称容量/Nominal capacity	100Ah
电量/Electric quantity	5KWh
电芯类型/Cell type	磷酸铁锂(LFP)
循环寿命/Cycle life	≥3000周(80%DOD)
充电温度范围/Charge temperature range	0~65°C
放电温度范围/Discharge temperature range	-20~65°C
最大持续充电电流/Maximum continuous charge current	50A
最大持续放电电流/Maximum continuous discharge current	80A
颜色/Colour	白(White)
尺寸/Dimensions	700×480×400MM
重量/Weight	约65Kg
安装方式/Installation method	落地式(Floor type)



比能量高  
Higher specific energy



稳频恒压交流电输出  
Stable frequency constant voltage AC output



循环寿命长  
Long cycle life



方便移动  
Easy to move



环保无污染  
Environmental protection and no pollution



支持深度定制  
Support deep customization

SNE-5KWh- II



逆变器参数/Inverter parameters

额定功率/Rated power	3KW
峰值功率/Peak power	5KW
输出波形/Output waveform	纯正弦波(Pure sine wave)
输入/输出交流电压/Input/Output AC voltage	110Vac/220Vac
输入/输出交流电压频率/Input/Output AC voltage frequency	50Hz/60Hz
逆变器类型/Type of inverter	高频(High frequency)

电池参数/Battery parameters

标称电压/Nominal voltage	51.2V
标称容量/Nominal capacity	100Ah
电量/Electric quantity	5KWh
电芯类型/Cell type	磷酸铁锂(LFP)
循环寿命/Cycle life	≥3000周(80%DOD)
充电温度范围/Charge temperature range	0~65°C
放电温度范围/Discharge temperature range	-20~65°C
最大持续充电电流/Maximum continuous charge current	45A
最大持续放电电流/Maximum continuous discharge current	45A
颜色/Colour	黑白(Black and white)
尺寸/Dimensions	850×650×215MM
重量/Weight	约60Kg
安装方式/Installation method	壁挂式(Wall mounted)



比能量高  
Higher specific energy



稳频恒压交流电输出  
Stable frequency constant voltage AC output



循环寿命长  
Long cycle life



安装方便  
Easy to install



环保无污染  
Environmental protection and no pollution



支持深度定制  
Support deep customization