

400W/27V Monocrystalline Silicon Solar Module Specifications

Item No.	G10M400-54H-V
Cell Type	Mono
Number of Cells	108pcs
Maximum Peak Power	400W
Maximum Power Voltage	31.10V
Maximum Power Current	12.87A
Open Circuit Voltage	37.00V
Short Circuit Current	13.77A
Cell Efficiency	≥22.9%
Module Efficiency	≥20.5%
Output Power Tolerance	0~+5W
Operating Temperature	-40℃~+85℃
Maximum System Voltage	1500VDC (IEC)
Maximum Series Fuse Rating	25A
Nominal Operation Cell Temperature	45±2℃
Temperature Coefficient of Pmax	-0.35%/℃
Temperature Coefficient of Voc	-0.27%/℃
Temperature Coefficient of Isc	+0.048%/℃
Front Side Maximum Static Loading	5400Pa
Rear Side Maximum Static Loading	2400Pa
Hailstone Test	25mm hailstone at the speed of 23m/s
Standard Test Conditions	AM1.5, 1000W/m ² , 25℃
Front Glass	Tempered glass, 3.2mm in thickness
Frame	Anodized aluminium alloy
Junction Box	≥IP68
Output Cables	300mm
Connector	MC4
Module Dimension	1722×1134×30mm
Module Weight	20.7kg
Packaging	37pcs/pallet
Product Certificates	TUV, CE, CQC,IEC



