
## ATK 600 Baling Press


Take control and convert your dry recyclable packing waste into manageable bales. Recyclers and industrial users of a ATK vertical baler benefit from waste volume reduction; storage, handling and transportation savings; avoidance of ever-increasing landfill charges; the satisfaction of environmental benefits and even possibly the generation of an additional revenue yield.


## **ATK 600 Baling Press**

- 12 month warranty
- √ 1500mm wide feed aperture
- Can be sited outside
- Available in 32 amp 3-phase or 16amp single phase electrics
- √ 50 Tonne press force
- √ 5 wire tying for a secure bale
- ✓ Automatic bale ejection
- ✓ Bale weights up to 650kg
- ✓ CE approved
- Fitted retaining claws to prevent material spring back
- ✓ Powder coated finish for durability










Press Force	50 Tonnes
Loading Aperture (H x W x D)	883 x 1500 x 1100mm
Bale Weight	up to 650 Kg
Bale Dimensions (H x W x D)	1100 x 1500 x 1100mm
Cycle Time	40 seconds
Noise	74 decibels
Machine weight	1930 Kg
Power Supply (kW-V-Hz)	32amp 3 Phase 11kW-400V-50Hz
Overall Dimensions (H x W x D)	3217 x 2103 x 1524mm
Optional Transportation Height	2500mm



Operating Voltage – 400v.

Frequency – 50hz.

32amp three phase five pin – A + N + PE

MCB (Minature circuit breaker) if fitted – Cat C or above.