

WASTE BALING PRESS

Baler ARTechnic PBPe200-o



Advantages of the machine:

- Feed hopper adapted to individual customer needs
- The moving of the pressing plate is kept extremely rigid and straight. The hydraulic cylinder does not take the bending forces from the pressing plate, which could lead to its damage. These forces are taken over by special plastic guides which are tailored to the corners of the chamber. The guides are made from specially chosen plastic, which is characterized by very high resistance to abrasion. Therefore, these elements are extremely durable. This avoids the need to control the tilt of the pressing plate. Because of all this you can easily exploit our machines, even for very demanding materials, without worrying of an improperly use of the machine.
- **The steel construction** of our machines is designed to withstand loads far in excess of the rated load for the different models (this is why our machines have a generally bigger own mass compared to the competition
- A system to prevent the decompressing of material after subsequent cycles of work.
- Possibilty to bind the packages (bales) with all commonly used materials like a polyester tape, twine or steel wire;
- The possibility of producing specified machines concerning the customer's request e.g. changes in the stroke of the pressing plate, changes in the loading hole, changes in the size of the bale, etc.
- Possibility to choose the version of the controller and to choose additional options, depending on individual needs
- Unmanned and durable hydraulic system
 - No hidden costs of operating the machine

Technical specification					
Number of chambers:	single	Loading:	top		
Charging hole:	1000 x 700 mm	Bale tying:	manual		
Max. pressure:	200kN (20 tons)	Bale launch:	automatic		
Unit pressure:	3,57 kg/cm ²	Supply:	400/50 [V/Hz]		
Bale dimensions:	800 x 700 x 800-1000(reg.)	Engine power:	5,5 kW		
Bale weight:	ca. 150 – 250 kg	Work cycle:	ca. 38 sekunds		
Productivity:	ca. 3 bale/h	Weight:	4500 kg		

Dimension				
	LEGEND		[mm]	
	A	length	5050	
	В	height	2120	
	С	width	1350	
C	D	filling inlet	1000×700	


Available steering types

Steering x (EXTRA)

Features

- Controller PLC
- Automatic digital steering of the work cycle
- Finished-bale signal
- LCD display
- Stepless maximum pressure regulation with 1 ton progression
- Stepless bale height regulation with 2 cm progression
- Daily/weekly/monthly statistics the readout of the number of finished bales with their weight estimation
- Different programs for different materials
- Possibility of regulating the length of time for which the pressing plate stays in the lower position
- NEW !! The ability to connect the machine to the statArtechnic

Control Panel



- 1. Main switch with the possibility to lock in position "0" (prevents from an use of the machine by unauthorized persons)
- 2. The white light "PACKET" indicates that the press has achieved the maximum filling
- 3. LCD and control panel
- 4. The green light "POWER" indicates a connection of the bale to power and that the main switch is turned ON
- 5. Emergency "STOP" switch
- 6. Button "START" starts the pressing process
- 7. Buttons "THROW-OFF". Two-handed operation controler for the bale ejector

Gallery





Contact

Headquater	Phones	E-mail and Web Site
ARTechnic ul. Gen. St. Maczka 9 43-300 Bielsko-Biała Poland	Tel. +48 (33) 816 01 69 fax +48 (33) 443 20 46	biuro@artechnic.pl www.artechnic.pl www.belowniceuzywane.pl