

 $\mathcal{A}$ 

This Low Profile vertical-downstroke unit is designed for customers with limited space while still producing up to 700 lbs. of OCC. This is a multi-material machine capable of baling paper, plastic, fiber, OCC and Non-Ferrous metals and other commercial applications.

## **Ideal for**

- Grocery Stores
- Home Retailers
- Pharmacies
- Big Box Retailers
- National Accounts
- Commissaries

- Warehouses
- Distribution Centers
- Hospitals, Schools & Universities
- Recyclers



## Order Today: (877) 506-BACE or visit us online at www.bacecorp.com

322 West 32nd Street Charlotte, NC. 28206

BACE Vertical Balers meet or exceed all existing ANSI & OSHA Safety Standards and are totally 100% ETL & CETL Approved.



## LEARN MORE AT WWW.BACECORP.COM


Toll Free: (877) 506-BACE (2223) = Fax: (704) 394-2210 BACE equipment meets or exceeds ANSI standard Z245.5.





# **BACE Vertical Baler V63HDLP**

#### DIM. (in./mm)

- **A.** 36/914
- **B.** 87/2210
- **C.** 43/1092
- **D.** 105/2667
- **E.** 92.5/2350







## **SPECIFICATIONS**

PERFORMANCE	
Nominal Bale Size	60" x 30" x 30"
Bale Weight	Up to 700 lbs OCC
Bale Volume	50 cu. ft.
No. of Bale Tie Slots	6
Compact Force Ibs - Normal / Maximum	62,203
Platen Pressure	36 PSI
Average Cycle Time	25 Seconds
Loading Height	49.50"
Ejector System	Semi-Automatic
Full Bale Switch	Standard

#### **HYDRAULIC / ELECTRICAL**

Motor HP	10
Voltage 3 Phase	208V, 230V, 480V
Full Load Amps (A = Amps)	32A, 28A, 14A
Pump GPM	15
Normal System Pressure PSI	2200
Cylinder Bore x Stroke	6" x 30"
Hydraulic Tank-Capacity Gallons	22

Due to continual product improvement BACE reserves the right to change specifications without notice. The information and pictures used in the document are for illustrative purposes only. Printed on recycled paper.

#### **Available Options**

- Slotted Front Door
- Wire Guides (allows for front bale tie-off)
- Rear Feed Opening,
  Front Eject
- Feed Chute
- Counter Weighted
  Floppy Retainer Dogs
- Oil Heater
- Weather Proof Package