

BALETECH®

6460

Horizontal Baler

STANDARD FEATURES

- 1/2" Thick Full Sheet Construction
- Hydraulic Door Cylinder
- 25 HP Tri-Volt 3 Phase
- Guide Wire Tie Tracks
- Multiple Use Shear Blade
- High Efficiency Hydraulic Assembly with Regenerative Hydraulics
- Stroke Saver Cycle Feature
- Nema 4 Rated Enclosures
- Standard Hopper
- Full Weld Construction
- Large Feed Hopper
- Logic Controlled Operation
- Dual Level Photo Eyes

WARRANTY ONE (1) YEAR PARTS AND LABOR, THREE (3) YEARS ON THE STRUCTURE

BALE WEIGHTS

<u>OCC</u> 1250 Lbs. (567 Kg)	<u>Office Paper</u> 1625 Lbs. (737 Kg)	<u>News</u> 1500 Lbs. (680 Kg)	<u>Magazines</u> 2025 Lbs. (918 Kg)	<u>PET</u> 920 Lbs (417 Kg)
<u>HDPE</u> 1150 Lbs (521 Kg)	<u>Alum. Can</u> 870 Lbs. (394 Kg)	<u>Misc N.F.</u> 1,200 Lbs. (544 Kg)		

SPECIFICATIONS

STRUCTURAL

Hopper Opening	60" W x 84" L
Feed Chamber	60" W x 64"L
Chamber Floor	3/4" Thick Full Sheet Construction
Chamber Sidewalls	1/2" Thick Full Sheet Construction
Shipping Weight	25,500 Lbs. Shipping Weight(11,566 Kg)

PERFORMANCE DATA

Main Cylinder	8" Bore x 120" Stroke x 5" Rod (20 cm) (304 cm)
Door Cylinder	4" Bore x 6" Stroke
Oil Reservoir	160 Gal (605 Liters)
Pump	43 Gal. Vane Pump (162 Liters)
Motor	TEFC 25 HP 208, 220, 480 Volts 3 Phase
Hyd. System Pressure	3,000 PSI (207 Bar)
Platen Force	150,800 Lbs.
Platen PSI	83 PSI. (6.0 Bar)
Cycle Time Adjustable	30 Sec - 18 Sec Stoke Saver
Bale Size	60 x 30 x 48

DIMENSIONS

HEIGHT

Frame 47.5" (120 cm) (1.21 m)

WIDTH

6' 1" (186 cm) (1.86 m)

LENGTH

25 Ft (762 cm) (7.62 m)

OPTIONAL FEATURES

- Bob Cat Feed Hopper
- Above Ground Conveyor
- Conveyor Feed Hopper
- Pit Conveyor

www.balettech.com

Distributed By :