

Horizontal semi-automatic hydraulic baler series



DATA SHEET

Model	Hydraulic power (Ton)	Bale Size (W*H*L) mm	Feed opening size (L*W) mm	Bale weight (Kg)	Bale lines	Out-bale way	Voltage (Customizable) (V/Hz)	Power (Kw/Hp)	Machine size (L*W*H) mm
JPW40BC	40	720*720*(300-1000)	1000*720	250-350	4	one-off bale out	380V/50Hz	15Kw/20Hp	5830*1250*1850
JPW60BC	60	1000*750*(300-1100)	1200*1000	350-500	4	one-off bale out	380V/50Hz	18.5Kw/25Hp	6350*1550*1940
JPW80BC	80	1100*800*(300-1100)	1350*1100	500-600	4	one-off bale out	380V/50Hz	22Kw/30Hp	7380*1850*2250
JPW100BC	100	1100*1200*(300-1100)	1500*1100	600-800	5	one-off bale out	380V/50Hz	30Kw/40Hp	8100*1850*2250

* The above parameters can be customized to customer's requirement.

CUSTOMERS CASE



<http://en.csj-baler.com>

ADD: 9th Floor, #6 Building, Lane 299, West Jiang Chang Road, Shanghai, China
 Factory: No.1, East Xinyuan Road, High-tech Park, Rugao, Jiangsu China

E-mail: jiaying@shjiaying.com

Mob: 0086-15921039980

Horizontal semi-automatic hydraulic baler series

Scope:

Suitable for a variety of conventional materials like paperboard, plastic, fiber, sponge, cloth, etc; widely used in a variety of factories and recycling industries.

PRODUCT INTRODUCTION

Closed type left-right door-open structure to make the bale be more compaction. It's strength door design, Hydraulic door locking, safety and convenient. PLC control system, operated by electric buttons, with feeding detection, can compress the material automatically.

The bale length can be set and packaging reminding device automatically. Every iron or bale sling is stringed by labor only one time to finish packaging. Saving the labor cost.

Bale size and voltage could be customized according to customer's requirements, different bale weight depends on different materials.

Three phase voltage and safety interlock device, simple operation, can connect with air-blower or conveyor line to feed material directly to improve efficiency.

PRODUCT PICTURES



<http://en.csj-baler.com>

ADD: 9th Floor, #6 Building, Lane 299, West Jiang Chang Road, Shanghai, China
 Factory: No.1, East Xinyuan Road, High-tech Park, Rugao, Jiangsu China

E-mail: jiaying@shjiaying.com

Mob: 0086-15921039980